Case File Number: REV120011-R01 (Revision of case file REV120011)

October 1, 2014

Location: 6450 Camden Street (See map on reverse)

Assessors Parcel Numbers: (039-3282-001-08)

A revision of a previously granted Conditional Use Permit and

Proposal: Design Review that would co-locate the addition of three (3)

new antennas at a site with existing antennas for a total of 18

antennas and associated equipment.

Applicant: Sprint c/o Phil Gamick

Contact Person: Phil Gamick **Phone Number:** (530)386-5253

Owner: Evergreen Cemetery Association

Case File Number: REV120011-R01

Planning Permits Required: Design Review for the co-location to install three (3) new

concealed telecommunication antennas and associated

equipment at a Macro telecommunication facility in the RM-1

zone.

Major Conditional Use Permit for the expansion of a Macro telecommunication facility within 100 feet of a residential zone.

General Plan: Urban Open Space

Zoning: RM-1 Mixed Housing Type Residential

Environmental Exempt, Section 15301 of the State CEQA Guidelines; minor

Determination: alterations to an existing facility

Exempt, Section 15303 of the State CEQA Guidelines; new

construction of small structures.

Section 15183 of the State CEQA Guidelines; projects consistent with a community plan, general Plan or zoning.

Historic Status: No Historic Record

Service Delivery District: 5 City Council District: 6

Date Filed: 6/16/14

Finality of Decision: Appealable to City Council within 10 days


For Further Information: Contact case planner Michael Bradley at (510) 238-36935 or

mbradley@oaklandnet.com

SUMMARY

The following staff report addresses the proposal for the addition to an unmanned wireless telecommunication facility located on the rooftop of an existing cemetery building, with the associated equipment cabinets located in a gated area on the ground next to the building. The project is for the addition of three (3) panel antennas with associated equipment at a site with 18 existing antennas. Given the number of antennas and the type of installation, this would be considered a "Macro" Telecommunications Facility. The facility is located within the center of a cemetery, on the roof of an existing cemetery building. The site is located in the RM-1 Mixed Housing Type Residential Zone. The General Plan designation for the site is Urban Open Space.

CITY OF OAKLAND PLANNING COMMISSION



Case File: REV120011-R01

Applicant: Sprint, Phil Gamick of Forza Telecom

Address: 6450 Camden Street

Zone: RM-I

Case File Number: REV120011-R01

Page 3

TELECOMMUNICATIONS BACKGROUND

Limitations on Local Government Zoning Authority under the Telecommunications Act of 1996 Section 704 of the Telecommunications Act of 1996 (TCA) provides federal standards for the siting of "Personal Wireless Services Facilities." "Personal Wireless Services" include all commercial mobile services (including personal communications services (PCS), cellular radio mobile services, and paging); unlicensed wireless services; and common carrier wireless exchange access services. Under Section 704, local zoning authority over personal wireless services is preserved such that the FCC is prevented from preempting local land use decisions; however, local government zoning decisions are still restricted by several provisions of federal law.

Under Section 253 of the TCA, no state or local regulation or other legal requirement can prohibit or have the effect of prohibiting the ability of any entity to provide any interstate or intrastate telecommunications service.

Further, Section 704 of the TCA imposes limitations on what local and state governments can do. Section 704 prohibits any state and local government action which unreasonably discriminates among personal wireless providers. Local governments must ensure that its wireless ordinance does not contain requirements in the form of regulatory terms or fees which may have the "effect" of prohibiting the placement, construction, or modification of personal wireless services.

Section 704 also preempts any local zoning regulation purporting to regulate the placement, construction and modification of personal wireless service facilities on the basis, either directly or indirectly, on the environmental effects of radio frequency emissions (RF) of such facilities, which otherwise comply with FCC standards in this regard. See, 47 U.S.C. 332(c)(7)(B)(iv) (1996). This means that local authorities may not regulate the siting or construction of personal wireless facilities based on RF standards that are more stringent than those promulgated by the FCC.

Section 704 mandates that local governments act upon personal wireless service facility siting applications to place, construct, or modify a facility within a reasonable time. 47 U.S.C.332(c)(7)(B)(ii). See FCC Shot Clock ruling setting forth "reasonable time" standards for applications deemed complete.

Section 704 also mandates that the FCC provide technical support to local governments in order to encourage them to make property, rights-of-way, and easements under their jurisdiction available for the placement of new spectrum-based telecommunications services. This proceeding is currently at the comment stage.

For more information on the FCC's jurisdiction in this area, contact Steve Markendorff, Chief of the Broadband Branch, Commercial Wireless Division, Wireless Telecommunications Bureau, at (202) 418-0640 or e-mail "smarkend@fcc.gov".

PROJECT DESCRIPTION

The applicant (Sprint) is proposing to install three (3) new panel antennas, with three new RRH's and other associated equipment. The proposal for the equipment shelters to be located in a gated area on the ground next to the building. All proposed antennas and associated equipment will not be accessible to the public.

(See Attachment A)

Page 4

PROPERTY DESCRIPTION

The subject property is a lot of approximately 25.02 Acres with a large cemetery building. The lot has frontage on Camden Street, 64th Avenue, MacArthur Boulevard. The subject property has a fully functioning cemetery on the site. Currently there are other telecommunication providers at the site.

GENERAL PLAN ANALYSIS

The Subject property is located within the Urban Park and Open Space General Plan designation. The Urban Park and Open Space land use classification is intended to identify, enhance and maintain land for parks and open space. Its purpose is to maintain an urban park, school yard, and garden system which provides open space for outdoor recreation, psychological and physical well-being, and relief from the urban environment. The proposed addition to an existing unmanned wireless telecommunication facility will not adversely affect and detract from the civic, commercial or residential characteristics of the neighborhood, because the antennas will be mounted on the roof of a cemetery building located in the center of a 25.02 acre cemetery.

ZONING ANALYSIS

The subject property is located within the RM-1 Mixed Housing Type Residential Zone-1. The intent of the RM-1 zone is to create, maintain, and enhance residential areas characterized by a mix of single family homes, duplexes, and neighborhood businesses where appropriate. Consistent with the intent of the RM-1 Zone the proposed development will be compatible with, and will not adversely affect, the livability or appropriate development of abutting properties and the surrounding neighborhood, with consideration to be given to harmony in scale, bulk, coverage and density.

ENVIRONMENTAL DETERMINATION

The California Environmental Quality Act (CEQA) Guidelines lists the projects that qualify as categorical exemptions from environmental review. The proposed project is categorically exempt from the environmental review requirements pursuant to Section 15301, alterations to existing facilities, Section 15303, new construction of small structures and 15183, projects consistent with a community plan, general plan or zoning.

KEY ISSUES AND IMPACTS

1. Conditional Use Permit

Section 17.17.040 of the City of Oakland Planning Code requires a conditional use permit to install a Macro Telecommunication facility in the RM-1 zone. Furthermore, Section 17.134.020 defines a major and minor conditional use permit. Subsections (A)(3)(i) lists a Major Conditional Use Permit: "Any telecommunication facility in or within one hundred (100) feet of the boundary of any residential zone. The required findings for a major conditional use permit are listed and included in staff's evaluation as part of this report.

Case File Number: REV120011-R01 Page 5

2. Project Site

Section 17.128.110 of the City of Oakland Telecommunication Regulations indicate that new wireless facilities shall generally be located on designated properties or facilities in the following order of preference:

- A. Co-located on an existing structure or facility with existing wireless antennas.
- B. City owned properties or other public or quasi-public facilities.
- C. Existing commercial or industrial structures in non-residential zones.
- D. Existing commercial or industrial structures in residential zones.
- E. Other non-residential uses in residential zones.
- F. Residential uses in non-residential zones.
- G. Residential uses in residential zones.
- *Facilities locating on an A, B or C ranked preference do not require a site alternatives analysis.

Since the proposed project involves the Co-location on an existing structure or facility with existing wireless antennas, the proposed project meets (A).

3. Project Design

Section 17.128.120 of the City of Oakland Telecommunications Regulations indicates that new wireless facilities shall generally be designed in the following order of preference:

- A. Building or structure mounted antennas completely concealed from view.
- B. Building or structure mounted antennas set back from roof edge, not visible from public right-of way.
- C. Building or structure mounted antennas below roof line (facade mount, pole mount) visible from public right-of-way, painted to match existing structure.
- D. Building or structure mounted antennas above roof line visible from public right of-way.
- E. Monopoles.
- F. Towers.
- * Facilities designed to meet an A or B ranked preference do not require a site design alternatives analysis. Facilities designed to meet a C through F ranked preference, inclusive, must submit a site design alternatives analysis as part of the required application materials. A site design alternatives analysis shall, at a minimum, consist of:
- a. Written evidence indicating why each higher preference design alternative can not be used. Such evidence shall be in sufficient detail that independent verification could be obtained if required by the City of Oakland Zoning Manager. Evidence should indicate if the reason an alternative was rejected was technical (e.g. incorrect height, interference from existing RF sources, inability to cover required area) or for other concerns (e.g. inability to provide utilities, construction or structural impediments).

Case File Number: REV120011-R01 Page 6

City of Oakland Planning staff have reviewed and determined that the site selected is conforming to all other telecommunication regulation requirements. The project has met design criteria (A) since the antennas shall be mounted completely concealed behind an existing mechanical screen wall approximately 42 feet above the public right of way and will be setback from the edge of the building. The associated equipment shelters will have no visual impact since the equipment will be placed behind a gated area next to the building in the center of a 25.02 acre cemetery.

4. Project Radio Frequency Emissions Standards

Section 17.128.130 of the City of Oakland Telecommunication Regulations require that the applicant submit the following verifications including requests for modifications to existing facilities:

- a. With the initial application, a RF emissions report, prepared by a licensed professional engineer or other expert, indicating that the proposed site will operate within the current acceptable thresholds as established by the Federal government or any such agency who may be subsequently authorized to establish such standards.
- b. Prior to commencement of construction, a RF emissions report indicating the baseline RF emissions condition at the proposed site.
- c. Prior to final building permit sign off, an RF emissions report indicating that the site is actually operating within the acceptable thresholds as established by the Federal government or any such agency who may be subsequently authorized to establish such standards.

The applicant states that the proposed project meets the radio frequency (RF) emissions standards as required by the regulatory agency. Submitted with the initial application was a RF emissions report, prepared by Hammett & Edison, Inc. (attachment B). The report states that the proposed project will comply with the prevailing standards for limiting public exposure to radio frequency energy and, therefore, will not cause a significant impact on the environment. Additionally, staff recommends that prior to the final building permit sign off, the applicant submits certified RF emissions report stating that the facility is operating within acceptable thresholds established by the regulatory federal agency.

CONCLUSION

City of Oakland planning staff believes that the proposed project and subject property can be developed to meet the established zoning and telecommunication regulations that were created and adopted to set certain criteria minimums and maximums for similar types of developments. Staff believes that the findings for approval can be made to support the Conditional Use Permit and Design Review.

Case File Number: REV120011-R01

Page 7

RECOMMENDATIONS:

- 1. Affirm staff's environmental determination
- 2. Approve Conditional Use Permit and Design Review application REV120011-R01 subject to the attached findings and conditions of approval

Prepared by:

Michael Bradley

Planner I

Approved by:

Robert D. Merkamp

Development Planning Manager

Approved for forwarding to the City Planning Commission

Darin Ranelletti, Deputy Director

Bureau of Planning

ATTACHMENTS:

- A. Project Plans & Photo simulation
- B. Hammett & Edison, Inc. RF Emissions Report

Page 8

FINDINGS FOR APPROVAL

FINDINGS FOR APPROVAL:

This proposal meets all the required findings under Section 17.134.050, of the General Use Permit criteria; all the required findings under Section 17.136.050.(B), of the Non-Residential Design Review criteria; all the required findings under Section 17.128.070(B), of the telecommunication facilities (Macro) Design Review criteria; and all the required findings under Section 17.128.070.(C), of the telecommunication facilities (Macro) Conditional Use Permit criteria; and as set forth below and which are required to approve your application. Required findings are shown in **bold** type; reasons your proposal satisfies them are shown in normal type.

SECTION 17.134.050 – MAJOR CONDITIONAL USE PERMIT FINDINGS:

A. That the location, size, design, and operating characteristics of the proposed development will be compatible with, and will not adversely affect, the livability or appropriate development of abutting properties and the surrounding neighborhood, with consideration to be given to harmony in scale, bulk, coverage, and density; to the availability of civic facilities and utilities; to harmful effect, if any upon desirable neighborhood character; to the generation of traffic and the capacity of surrounding streets; and to any other relevant impact of the development.

The location, size, design and operational characteristics of the proposal will not adversely affect the livability or appropriate development of abutting properties and the surrounding neighborhood. Consideration was given to the harmony in scale, bulk, and coverage; to the availability of civic facilities and utilities; to harmful effect, if any, upon desirable neighborhood character; to the generation of traffic and the capacity of surrounding streets; and to any other relevant impact of the development. The proposed telecommunications antennas will be located behind mechanical screening wall on the roof of the existing building and will not adversely affect the operating characteristic or livability of the existing area. The facility will be unmanned and will not create additional vehicular traffic in the area.

B. That the location, design, and site planning of the proposed development will provide a convenient and functional living, working, shopping, or civic environment, and will be as attractive as the nature of the use and its location and setting warrant.

The location, design and site planning of the proposed development will not detract from the existing civic environment and will preserve the existing character of the site by screening the new telecom facilities out of view from the general public

C. That the proposed development will enhance the successful operation of the surrounding area in its basic community functions, or will provide an essential service to the community or region.

The proposed development will enhance the successful operation of the surrounding area in its basic community function and will provide an essential service to the community or region. This will be achieved by improving the functional use of the site by providing a regional

Page 9

telecommunication facility for the community and will be available to police, fire, public safety organizations and the general public.

D. That the proposal conforms to all applicable design review criteria set forth in the DESIGN REVIEW PROCEDURE of Chapter 17.136 of the Oakland Planning Code.

The proposal conforms with all significant aspects of the design review criteria set forth in Chapter 17.136 of the Oakland Planning Code, as outlined below.

E. That the proposal conforms in all significant respects with the Oakland General Plan and with any other applicable plan or development control map which has been adopted by the City Council.

The Subject property is located within the Urban Park and Open Space General Plan designation. The Urban Park and Open Space land use classification is intended to identify, enhance and maintain land for parks and open space. Its purpose is to maintain an urban park, school yard, and garden system which provides open space for outdoor recreation, psychological and physical well-being, and relief from the urban environment. The proposed unmanned wireless telecommunication facility will not adversely affect and detract from the civic, commercial or residential characteristics of the neighborhood, because the antennas will be mounted on the roof of a cemetery building located in the center of a 25.02 acre cemetery.

<u>17.136.050(B) – NONRESIDENTIAL DESIGN REVIEW CRITERIA:</u>

1. That the proposal will help achieve or maintain a group of facilities which are well related to one another and which, when taken together, will result in a well-composed design, with consideration given to site, landscape, bulk, height, arrangement, texture, materials, colors, and appurtenances; the relation of these factors to other facilities in the vicinity; and the relation of the proposal to the total setting as seen from key points in the surrounding area. Only elements of design which have some significant relationship to outside appearance shall be considered, except as otherwise provided in Section 17.136.060;

The proposal is the expansion of a macro telecommunications facility which includes three (3) new panel antennas, three (3) new RRH's and other associated equipment. The proposed antennas will be placed behind an existing mechanical screening wall and therefore will be consistent and well related to the surrounding area in scale, bulk, height, materials, and textures. The antennas will also be located on a cemetery building located in the center of a 25.02 acre lot and will not be visible from the street.

2. That the proposed design will be of a quality and character which harmonizes with, and serves to protect the value of, private and public investments in the area;

The design will be appropriate and compatible with current zoning and general plan land use designations. The proposal protects and preserves the surrounding neighborhood context by adding wireless telecommunication antennas to a residential area. The antennas will be concealed from public view and will not have any visual impact on the neighborhood.

Case File Number: REV120011-R01

Page 10

3. That the proposed design conforms in all significant respects with the Oakland General Plan and with any applicable design review guidelines or criteria, district plan, or development control map which have been adopted by the Planning Commission or City Council.

The proposal conforms with the City of Oakland Comprehensive General Plan meeting specific General Plan policies and the Supplemental Report and Recommendations on Revisions to the Citywide Telecommunications Regulations. The proposal will conform to performance standards for noise set forth in Section 17.120.050 for decibels levels in residential areas for both day and nighttime use. The Project conforms to all macro-facility definitions set forth in Section 17.128.070 and meets all design review criteria to minimize all impacts throughout the neighborhood

17.128.070(B) DESIGN REVIEW CRITERIA FOR MACRO FACILITIES

- B. Design Review Criteria for Micro Facilities. In addition to the design review criteria listed in <u>Chapter 17.136</u>, the following specific additional criteria must be met when design review is required before an application can be granted:
- 1. Antennas should be painted and/or textured to match the existing structure.

The antennas will be mounted behind an existing screening wall on the top of an existing cemetery building located in the center of a 25.02 acre lot and will not be visible from the street.

2. Antennas mounted on architecturally significant structures or significant architectural details of the building should be covered by appropriate casings which are manufactured to match existing architectural features found on the building.

The antennas will be mounted behind an existing screening wall on the top of an existing cemetery building located in the center of a 25.02 acre lot and will not be visible from the street.

3. Where feasible, antennas can be placed directly above, below or incorporated with vertical design elements of a building to help in camouflaging.

The antennas will be mounted behind an existing screening wall on the top of an existing cemetery building located in the center of a 25.02 acre lot and will not be visible from the street.

4. Equipment shelters or cabinets shall be screened from the public view by using landscaping, or materials and colors consistent with surrounding backdrop or placed underground or inside existing facilities or behind screening fences.

The equipment cabinets will be located inside a locked and screened gated area next to the existing building and will not be visible from public view.

5. Equipment shelters or cabinets shall be consistent with the general character of the area.

The equipment cabinets will be located inside a locked and screened gated area next to the existing building and will not be visible from public view.

6. For antennas attached to the roof, maintain a 1:1 ratio (example: ten feet high antenna requires ten feet setback from facade) for equipment setback; screen the antennas to match existing air conditioning units, stairs, or elevator towers; avoid placing roof mounted antennas in direct line with significant view corridors.

The proposed replacement antennas will be mounted on existing pole mounts that are setback back from the edge of the roof and are located behind an existing mechanical screening wall.

7. That all reasonable means of reducing public access to the antennas and equipment has been made, including, but not limited to, placement in or on buildings or structures, fencing, anti-climbing measures and anti-tampering devices.

The antennas will be mounted to the roof and will not be accessible to the public due to its location. The equipment cabinets will be located inside a locked gated area next to the existing building.

17.128.070(B) CONDITIONAL USE PERMIT CRITERIA FOR MACRO FACILITIES

C. Conditional Use Permit Criteria for Macro Facilities. In addition to the conditional use criteria listed in <u>Chapter 17.134</u>, the following specific additional criteria must be met before a conditional use permit can be granted:

1. The project must be demonstrated to have no visual impact.

The antennas will be mounted behind an existing screening wall on the top of an existing cemetery building located in the center of a 25.02 acre lot and will not be visible from the street.

2. The project must meet the special design review criteria listed in subsection B of this section.

The proposed project meets the special design review criteria listed above in section 17.128.070B.

Case File Number: REV120011-R01

Page 12

CONDITIONS OF APPROVAL REV120011-R01

STANDARD CONDITIONS:

1. Approved Use

Ongoing

- a) The project shall be constructed and operated in accordance with the authorized use as described in the application materials, REV120011-R01, and the plans dated May 29, 2014 and submitted on June 16, 2014 and as amended by the following conditions. Any additional uses or facilities other than those approved with this permit, as described in the project description and the approved plans, will require a separate application and approval. Any deviation from the approved drawings, Conditions of Approval or use shall required prior written approval from the Director of City Planning or designee.
- b) This action by the City Planning Commission ("this Approval") includes the approvals set forth below. This Approval includes: The addition to a Macro telecommunications facility located on an existing building at 6450 Camden Street (APN: 039-3282-001-08), under Oakland Municipal Code 17.128, 17.136 and 17.134.

2. Effective Date, Expiration, Extensions and Extinguishment Ongoing

Unless a different termination date is prescribed, this Approval shall expire **two calendar years** from the approval date, unless within such period all necessary permits for construction or alteration have been issued, or the authorized activities have commenced in the case of a permit not involving construction or alteration. Upon written request and payment of appropriate fees submitted no later than the expiration date of this permit, the Director of City Planning or designee may grant a one-year extension of this date, with additional extensions subject to approval by the approving body. Expiration of any necessary building permit for this project may invalidate this Approval if the said extension period has also expired.

3. Scope of This Approval; Major and Minor Changes Ongoing

The project is approved pursuant to the Oakland Planning Code only. Minor changes to approved plans may be approved administratively by the Director of City Planning or designee. Major changes to the approved plans shall be reviewed by the Director of City Planning or designee to determine whether such changes require submittal and approval of a revision to the approved project by the approving body or a new, completely independent permit.

4. Conformance with other Requirements

Prior to issuance of a demolition, grading, P-job, or other construction related permit

a) The project applicant shall comply with all other applicable federal, state, regional and/or local codes, requirements, regulations, and guidelines, including but not limited to those imposed by the City's Building Services Division, the City's Fire Marshal, and the City's Public Works Agency.

Page 13

b) The applicant shall submit approved building plans for project-specific needs related to fire protection to the Fire Services Division for review and approval, including, but not limited to automatic extinguishing systems, water supply improvements and hydrants, fire department access, and vegetation management for preventing fires and soil erosion.

5. <u>Conformance to Approved Plans; Modification of Conditions or Revocation</u> **Ongoing**

- a) Site shall be kept in a blight/nuisance-free condition. Any existing blight or nuisance shall be abated within 60-90 days of approval, unless an earlier date is specified elsewhere.
- b) The City of Oakland reserves the right at any time during construction to require certification by a licensed professional that the as-built project conforms to all applicable zoning requirements, including but not limited to approved maximum heights and minimum setbacks. Failure to construct the project in accordance with approved plans may result in remedial reconstruction, permit revocation, permit modification, stop work, permit suspension or other corrective action.
- c) Violation of any term, conditions or project description relating to the Approvals is unlawful, prohibited, and a violation of the Oakland Municipal Code. The City of Oakland reserves the right to initiate civil and/or criminal enforcement and/or abatement proceedings, or after notice and public hearing, to revoke the Approvals or alter these conditions if it is found that there is violation of any of the conditions or the provisions of the Planning Code or Municipal Code, or the project operates as or causes a public nuisance. This provision is not intended to, nor does it, limit in any manner whatsoever the ability of the City to take appropriate enforcement actions.

6. Signed Copy of the Conditions

With submittal of a demolition, grading, and building permit

A copy of the approval letter and conditions shall be signed by the property owner, notarized, and submitted with each set of permit plans to the appropriate City agency for this project.

7. Indemnification

Ongoing

- a) To the maximum extent permitted by law, the applicant shall defend (with counsel acceptable to the City), indemnify, and hold harmless the City of Oakland, the Oakland City Council, the City of Oakland Redevelopment Agency, the Oakland City Planning Commission and its respective agents, officers, and employees (hereafter collectively called City) from any liability, damages, claim, judgment, loss (direct or indirect)action, causes of action, or proceeding (including legal costs, attorneys' fees, expert witness or consultant fees, City Attorney or staff time, expenses or costs) (collectively called "Action") against the City to attack, set aside, void or annul, (1) an approval by the City relating to a development-related application or subdivision or (2) implementation of an approved development-related project. The City may elect, in its sole discretion, to participate in the defense of said Action and the applicant shall reimburse the City for its reasonable legal costs and attorneys' fees.
- b) Within ten (10) calendar days of the filing of any Action as specified in subsection A above, the applicant shall execute a Letter of Agreement with the City, acceptable to the Office of the

City Attorney, which memorializes the above obligations. These obligations and the Letter of Agreement shall survive termination, extinguishment or invalidation of the approval. Failure to timely execute the Letter of Agreement does not relieve the applicant of any of the obligations contained in this condition or other requirements or Conditions of Approval that may be imposed by the City.

8. Compliance with Conditions of Approval

Ongoing

The project applicant shall be responsible for compliance with the recommendations in any submitted and approved technical report and all the Conditions of Approval set forth below at its sole cost and expense, and subject to review and approval of the City of Oakland.

9. Severability

Ongoing

Approval of the project would not have been granted but for the applicability and validity of each and every one of the specified conditions, and if any one or more of such conditions is found to be invalid by a court of competent jurisdiction this Approval would not have been granted without requiring other valid conditions consistent with achieving the same purpose and intent of such Approval.

10. Job Site Plans

Ongoing throughout demolition, grading, and/or construction

At least one (1) copy of the stamped approved plans, along with the Approval Letter and Conditions of Approval, shall be available for review at the job site at all times.

11. Special Inspector/Inspections, Independent Technical Review, Project Coordination and Management

Prior to issuance of a demolition, grading, and/or construction permit

The project applicant may be required to pay for on-call special inspector(s)/inspections as needed during the times of extensive or specialized plancheck review, or construction. The project applicant may also be required to cover the full costs of independent technical and other types of peer review, monitoring and inspection, including without limitation, third party plan check fees, including inspections of violations of Conditions of Approval. The project applicant shall establish a deposit with the Building Services Division, as directed by the Building Official, Director of City Planning or designee.

12. Days/Hours of Construction Operation

Ongoing throughout demolition, grading, and/or construction

The project applicant shall require construction contractors to limit standard construction activities as follows:

- a) Construction activities are limited to between 7:00 AM and 7:00 PM Monday through Friday, except that pile driving and/or other extreme noise generating activities greater than 90 dBA shall be limited to between 8:00 a.m. and 4:00 p.m. Monday through Friday.
- b) Any construction activity proposed to occur outside of the standard hours of 7:00 am to 7:00 pm Monday through Friday for special activities (such as concrete pouring which may require more continuous amounts of time) shall be evaluated on a case by case basis,

Case File Number: REV120011-R01

Page 15

with criteria including the proximity of residential uses and a consideration of resident's preferences for whether the activity is acceptable if the overall duration of construction is shortened and such construction activities shall only be allowed with the prior written authorization of the Building Services Division.

- c) Construction activity shall not occur on Saturdays, with the following possible exceptions:
- i. Prior to the building being enclosed, requests for Saturday construction for special activities (such as concrete pouring which may require more continuous amounts of time), shall be evaluated on a case by case basis, with criteria including the proximity of residential uses and a consideration of resident's preferences for whether the activity is acceptable if the overall duration of construction is shortened. Such construction activities shall only be allowed on Saturdays with the prior written authorization of the Building Services Division.
- ii. After the building is enclosed, requests for Saturday construction activities shall only be allowed on Saturdays with the prior written authorization of the Building Services Division, and only then within the interior of the building with the doors and windows closed.
 - d) No extreme noise generating activities (greater than 90 dBA) shall be allowed on Saturdays, with no exceptions.
 - e) No construction activity shall take place on Sundays or Federal holidays.
 - f) Construction activities include but are not limited to: truck idling, moving equipment (including trucks, elevators, etc) or materials, deliveries, and construction meetings held on-site in a non-enclosed area.

14. Operational Noise-General

Ongoing

Noise levels from the activity, property, or any mechanical equipment on site shall comply with the performance standards of Section 17.120 of the Oakland Planning Code and Section 8.18 of the Oakland Municipal Code. If noise levels exceed these standards, the activity causing the noise shall be abated until appropriate noise reduction measures have been installed and compliance verified by the Planning and Zoning Division and Building Services.

PROJECT SPECIFIC CONDTIONS:

15. Radio Frequency Emissions

Prior to the final building permit sign off

The applicant shall submit a certified RF emissions report stating the facility is operating within the acceptable standards established by the regulatory Federal Communications Commission.

ATTACHMENT A

12657 Alcosta Bhd., Sulte 300 San Ramon, CA 94583 Sprint

2.5 EQUIPMENT DEPLOYMENT

PROJECT NAME:

SITE NAME:

THE SEMINARY

SF35XC001-A

CASCADE #:

SITE ADDRESS:

Sprint

6450 CAMDEN STREET OAKLAND, CA 94605

SITE TYPE:

ROOFTOP

These outline specifications in conjunction with the spirit standard construction specifications, including contract documents and the construction drawings describe the work to be performed by the contractor.

Section 01 100 - Scope of Work

The <u>Work:</u> Shat comply with applicable national codes and standards, latest edition, and portions thereof.

Proceedings cours between the stordard continuing specifications for wieless sites trabulating the storage continuing control courses. The storage continuing the storage continuing the storage of the storage continuing the storage of the storage continuing the storage of the

<u>Soli formed in the proposable for familiariting himsel with all contract documents, field conditions and demensions prior to proceeding with construction.</u>

On-Sile Supervision:
The control Supervise and direct he work and shall be responsible for construction means, the techniques, sequences, and proceedures in accordance with the control documents.

<u>Dravings, Specifications and detaits required at lobaties</u>.

Construction controlled systems of the jobatie from mobilization of the jobatie from mobilization through constitution completion of the jobatie from the beginning of the construction completion.

Details are intended to two edigit lates, two-ded all materials and lates as nequired to provide compiles and functioning system, westlineation may be required to this jab dimensions or conditions, and such modifications shall be included as part of the way.

- Confracted ratio flowing spirit construction and an accordance of any confrience part by proceeding with the confidence of the process of th
- Mank the field set of drawings in red, documenting any changes from the construction documents.

Methods of Procedure (MOPs) for construction; Contractor shall perform work as described in the following installation and commissioning mops.

1. How to have a cooking is. How to harden a make a cooking is. How to harden a make a make a make a manage and in the cooking is a marked manage and in the cooking a marked manage and is a marked manage an

Section 01 200 - Company funished material and equipment Company lunished material and equipment is identified on the RF data street in the construction drawings.

Contractor is responsible for Sprint provided material and equipment to ensure it is protected and handled properly throughout the construction duration.

Contractor responsible for receipt of Sprint furnished equipment at cell site or contractors location. Contractor to complete shipping and receipt documentation in accordance with company practice.

Section 01 300 - Cell Site Construction Co.

Notice to Proceed: No work shall commence prior to company's willten notice to proceed and the issuance of work order.

Size Cleantiness:

Control to the way, control to a countialing water material debte, and total. At the completion at the way, control to the remover than the size of remaining tubbide, implements temporary localities, and surplus materials.

Section 01 400 - Submittals & Tests

Alemander

Althe company; request, any alternatives to the maleriate or methods specified shall be submitted to sphile company; request, any alternatives to the properties of manager for approach skiff will reflect willing. No webd approach wiff be condidered.

Willigh, No webd approach wiff be condidered.

Tests and inspections:

- A. The contractor shall be responsible for all construction tests, inspections and project documentation.
 - Confractor shall accomplish testing including but not limited to the following:
- Coax Sweeps and Fiber tests per TS-0200 Rev 4 antenna ine acceptance standards.
- Agi cairulit and downtill provide an automated report uploaded to Steno using a commercial model of the purpose electronic Antenna digramment local (AAI), installed adminuth, centerfine and downlift must conform with RF configuration data

3. Contractor shall be responsible for any and all corrections to any work identified as unacceptable in site inspection activities and/or as a result of testing.

C. Required closeout documentation includes, but is not limited to the following:

4. All festing required by applicable installation maps.

- 1. Azimuth, downtill, AGL from sunsight instruments Antenna Alignment Tool (AAT)
- Scanable barcode photographs of tower top and inaccessible serialized equipment Sweep and Fiber tests
 - 4. All available jurisdictional information
- PDF scan of redlines produced in field

All metal components shall be handled with core to prevent damage to the components, their preservative treatment, or their protective coatings.

2. If eld louchup paint shall be done in accordance with the manufacturer's written instructions.

Galvaniding damage and all bolls and nuts shall be touched up after lower erection with "Galvanox," Tay Galv," or 'Zanc-It."

- A PDF scan of redline mark-ups sultable for use in electronic As-Bull drawing production
- Lien waivers
 - Final payment application
- Required final construction photos
- 10. Construction and commissioning checklist complete with no deficient items
- All post NIP lasts including document uploads completed in Siterra (Sprint's document repository at record).
- Closeoul photographs:

a Provide pholographs of final project per the following ist. Additional pholographs may be required to support acceptance processes

- (i) Back main hybrid cable route (minimum two photos)
 - (iii) Manufacturer's name tag for all serialized equipment Of each anienna and RRH
- (iv) Pult and distribution boxes intermediate between RRH's and MMBS (door open)
- (v) MMBS Cabinel with door open showing modifications
- (vi) Power cabinet, doors open, batteries installed
- (vii) Break out cylinders
- (viii) ASR Signage for Sprint owned towers

(ix) Radiation exposure warning signs

- (x) Photograph from each sector from approximately RAD center of any new antenna at horizon.
- Load plotes to Sistem project liveny 5. In 5 cased new collegory, 25 perployment, and sellicing the moment Construction. Lotes photes with site eccepted ond view being despited, Comments and the their photographs shall GTS anabled such that the GTS coordinates are their designed in the photo meta-plotegraphs shall GTS anabled such that the GTS coordinates are their designed in the photo meta-plotegraphs are such as a s

Commissioning: Perform all commissioning as required by applicable MOPs

in<u>tegration:</u> Perform all integration activilies as required by applicable MOPs

Section 09 900 - Painting

- Comply with all environmental regulations for vokalile organic compounds.

Comply with governing codes and regulations. Provide products of acceptable manufactures which have been in audisdiactory use in strains service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's trathocilors.

 A. Manulacturers Benjamin Moore, Ici Devoe coolings, PPG, Sherwin Willams or approved equal.
 Provide premium grade, professional-quality praducts for coaling systems Paint Schedule:

- Belaior antennae and antenna mounting hardware. One acal of primer and two finish acads, Paint for antennaer stable benchmeredisc based and socialism meralicile professive. Throuside colors and adolence a required to mask appearance of antennae an adjacent bushing suffices and as acceptable to the owner. Reter to antenna manufacturer's instructions whenever possible.
 - Water Tonks: Touch up prepare surfaces to be repaired. Follow Industry standards and requirements of owner to match existing accoling and finish.

Inspect surfaces, report unsalisfactory conditions in writing: beginning work means acceptance of substrate. Comply with manufacturers instructions and recommendations for preparation, priming and coaling work. Coordinate with work of other sections.

ainting Application:

Match approved mack-ups for color, texture, and pattern. Re-coal or remove and replace work which does not match or shows loss of adhesion.

4. Clean up, touch up and protect work.


Touchup Painting:

12657 Alcosta Blvd., Suile 300 San Ramon, CA 94583

Sprint:









hybrid Cable: hybrid Cable and funished for frealbishon of eoch site. Coble shall be installed per the construction devings and the applicable manufacturer's requirements.

 $\frac{A \text{Allennos and RRH}_{\Sigma}}{\text{The number and bype of anlennos and RRHs}} \text{ to be installed is detailed on the construction drawings.}$

Summary: This section specifies installation of antennas, RRH's, and cable equipment, installation, and testing of cooxiditate cable.

Section 11 700 - Antenna assembly, Remote Radio Units and cable installation

| B.K.W. | снескер вт: |
|-----------|-------------|
| JVM | DRAWN BY: |
| 13065-105 | PROJECT NO: |

| _ | _ | _ | _ | _ | _ | _ |
|---|---|---|-------|---------------|---------------|-------------|
| | | | | 1 ASS CONTROL | NUMBER COSCIL | WE CHILDREN |
| | | | | 05/29/2014 | מלמלעק | MANAN. |
| | | | | 2 | - | Ŀ |

| | П | _ | | Г |
|--|----------------|------------------|----------------|-------------|
| | TOTAL CONTRAIN | MINE CO SIGNIEVE | YES CO SUSMETA | DESCRIPTION |
| | 102/22/20 | סלפלעק | \$178/JZ | DARE |
| | 2 | - | ۰ | چ |

100% CD Submitted 4102/62/50

The contractor shall route, test, and install all cables as indicated on the construction drawings and in accordance with the manufacturer's recommendations.

Hybrid Cables installation:

The installed radius of the cabbes shall not be less than the manufacturer's specifications for bending radii.

C. Extreme care shall be taken to avoid damage to the cables during handling and installan.

Antenna mounting requirements: Provide antenna mounting hardware as indicated on the drawings.

In econtractor shall position the antenna on lower pipe mounts so that the bottom strut is level, the
pipe mounts shall be plumb to within 1 degree.

The controcior shall assemble all anhennas analle in accordance with the instructions supplied by the monulacitoner. Antenno height, asimuth, and feed orientalian information shall be a designated on the continuation drawings.

<u>Miscellaneous:</u> Install spitters, combiners, filters per RF data sheel, furnished by Sprint. Remote Electrical Tilf (RET) cables: insert spec





Fastening main hybrid cables: All cables shall be permanently fastened to the coax ladder at 4.0° oc using non-magnetic stainless steel citps.

Fastening individual (ther and DC cables above breakout enclosure (medusa), within the MM\$\$ cabinet and any intermediate distribution boxes:

Elsert. Support Riber bundes using ½" veloca staps of the required length © 18" oc. Straps shall be UV, all and water resistant and suillable for industrial insidiations as manufactured by l'extol or approved exped.

DC: Support DC bundles with zip fies of the adequate length. Zip fies to be 11V stabilized, black nylon, with lensile strength at 12,000 psi as manufactured by Nelco products or equal.

Fostening jumpers. Secure jumpers to the side arms or head frames using stainless steel lie wraps or stainless steel bullerity clips.

Cable routing: Cable installation shall be planned to ensure that the lines will be properly routed in the cable envelop as indicated on the drawings. Avoid fwisting and acasaovers.

a. Inspect cable prior to use for shipping damage, notity the construction manager.

4. Cable installation:

က

Host cable using proper hoising grips. Do not exceed monutactures recommended moximum bend radius.

SF35XC001-A The Seminary

6450 CAMDEN STREET OAKLAND, CA 94605

GENERAL NOTES 1

GN-1

Confinue from GN-1

- 5. Grounding of transmission fines: All transmission lines shall be grounded as indicated on drawings. Hybrid Cable color coding: All color coding shall be as required in 15 0200 Rev 4.
- Hybrid Cable labeling: Individual Hybrid and DC bundles shall be labeled alpha-numerically according to Sprint cell site engineering notice EN 2012-001, Rev 1

Weatherproofing exterior connectors and hybrid cable ground kits:

- A. All fiber & coax connectors and ground kits shall be weatherproofed.
- Weatherprooled using one of the following methods. All installations must be dane in accordance with the manufacturer's recommendations and industry best practices.
 - Cold Shink: Encompass connector in cold shink tubing and provide a double wrap of 2* electrical tape extending 2* beyond tubing. Provide 3m cold shink CXS series or equal.
- Self-omolgamading tape: Clean suffices. Apply a double wap of self-amolgamading tape 2*
 Psychot connection Apply a socional wap of self-amolgamania to per longoste direction.
 Psychot double wap of 2* wide electrical tape selectring 2* beyond in self-amolgamaning tapes.
 - 3m slim lock closure 716: Substitutions will not be allowed.
- Open flame on job site is not acceptable

Section 11 800 - Installation of Multimodal Base Stations (MMBS) and related equipment

Summary:

- This section specifies MMBS cotainels, power catheols, and internal equipment including by not imited to recifines, power databullen units, base bond units, surge ornestons, battleries, and similar equipment funithed by the company for installation by the contraction (FACP).
- Contractor shall provide and install all miscellaneous materials and provide all labor required for professibility equipment in existing cabinet or new cobinet as shown an drawings and as required by the applicable infabilien maps.
- Comply with manufacturers installation and start-up requirements

DC Circuit Breaker labeling

A. Label circuit breakers according to Sprint cell site engineering notice - EN 2012-001, Rev 1.

Section 26 100 - Basic electrical requirements

<u>Summany:</u> This section specilies basic electrical requirements for systems and components.

Quality Assurance:

- All equipment famished under division 2s shall carry UL labels and listings where such labels and listings
 are available in the industry.
 - Manulacturers of equipment shall have a minimum of three years experience with their equipment installed and operating in the field in a use similar to the proposed use for this project.
- <u>Materials and equipment</u>: All materials and equipment specified in Division 28 of the same type shall be of the same manufacturer and shall be new, of the best quality and design, and free from defects

Supporting Devices:

- A. All equipment turnished under Division 26 shall carry UL tabels and Isilings where such labels and Isilings
 are available in the industry.
- Manufacturers of equipment shall have a minimum of three years experience with their equipment installed and operating in the field in a use similar to the proposed use for this project.
 - C. Motreck and equipment a pecified in Oxiden 26 of the same has shall be of the same manufacturer and shall be new, of the best quality and design, and free from defects.

Supporting Devices:

- An Manufactured structural support materials: Subject to compliance with requirements, provide products by the following:
- 1. Allied Tube and Conduil

 - 2. B-Line system
- 3. Sunistrut Diversified Products
- Fasteners: Types, materials, and construction features as follows:

S,

4. Thomas & Belts

- Power-driven threaded studs: Heat-freated steet designed specifically for the intended service. Expansion anchors: Corbon sleel wedge or sleeve type
- Toggle bolls on hollow masony units.

fasten by means of wood screws on wood.

- Concrete inserts or expansion boits on concrete or solid masonry.
- Machine screws, welded threaded studs, or spring-fension clamps on steel
- Explosive devices for attaching hangers to structure shall not be permitted.
- 8. Do not weld conduit, pipe straps, or items other than threaded studs to steel structures.
- in partitions of light sleet construction, use sheet metal screws.

Supporting Devices:

- install supporting devices to fasten electrical components securely and permanently in accordance with NEC.
- Coordinate with the building structural system and with other trades.
- Unless otherwise indicated on the drawings, tasten electrical items and their supporting hardware securely to the structure in accordance with the following: ပ
- D. Ensure that the load applied by any tastener does not exceed 25 percent of the proof test load. Use vibration and shock-resistant fasteners for attachments to concrete slabs.

Bectrical Identification:

- A. Update and provide typed circuit breaker scheduler in the mounting bracket, inside doors of AC patern boards with any changes made to the AC system.
- Branch circuits feeding aviation obstruction lighting equipment shall be clearly identified as such at the branch circuit paneboard.

Section 26 200 - Electrical materials and equipment

Conduit:

- A. Rigid polorised self self (RIS) concell a bette tured for eacher in colorise or grant of only in unfinished interior localitions and for encoact rust in concerde. Rigid consult and filtings shall be self-colorist with zinc existent and historist by the hold opplications are concerned. Consult shall be produced to ANSI specifications COOI. Lederal specification WW-COOI and shall be better with underwinder bloodings. Filtings are the treaded self-colorism WW-COOI and shall be better with underwinder bloodings. Filtings are the treaded self-colorism with colorism and coopelable. RCS conduit shall be manufactured by Alles & Republic or Winsoland.
- Underground conduil in concele shall be Polyvinytchloride (PVC) suitable for drect buriol os appicable. Linit shall be halled, and little havinel welded no accordance with manufacture's instruction. Conduil shall be Carlon electrical products or approved equal. ъ
- C. Transitions between PVC and rigid (RGS) shall be made with PVC exalled metalific long sweep radius elbows.
- But or rigid patwormed shocked in my be used in finished spoces conceded in wells and ceilings. But shall be noted seen description, which conceded in wells and ceilings are produced to ANS specification (2021, sectors specification with "CASA" and with the UL But should be manufactured to ANS specification (2021, sectors specification with "CASA" and with the UL But should be manufactured by the Case Republic, which is the produced equal tillings shall be meable; compression, set serve connections that had no accompression, set serve connections that had no accompression, set serve connections that had no accompanied.
- Liquid light leabbs meidlic conduit shall be used for find connection to equipment. Fillings shall be mentaling and representation of the properties of the properties of the properties of the properties of the connections and not be acceptable. Notamin neight of leable conduit shall not greened friend the first and professed and support the straylers by the "Manifolderiner al leable conduits shall be Card, Anacordo Medi Frence of University Medi Frence or approved equal.
- Minimum size conduit shall be 3/4 inch (21mm).

A. At entrances to cabinets or other equipment not having integral threaded hubs provide metaltic threaded hubs of the sec and configuration enquived, hub shall harbe because and neopenne oring seal. Provide impact residunt 105 degree or plastic bushings to profest cable insubilion.

Sprint

- Cable termination fittings for condult
- 1. Cable terminators for RGS conduits shall be type CRC by 0.7/Gedney or equal.
- Cable terminators for LFMC shall be £100 CL2075; or made for the purpose products by Roxlec.
- Exterior pull boxes and pull boxes in interior industrial areas shall be plated cost alloy, freavy duty, verolinerpool, dats proof, with spaster, plated from alloy cover and stainless sheel cover screws, arouse-linted who series or equal.
- Conduit outlet bodies strail be picted cast also, with similar gaskeled covers. Outlet bodies shall be of the configuration and size sultable for the application. Provide acouse-hinds form 8 or equal.
- Manufacturer for boxes and covers shalt be Holfmon, Square "d", Crouse-Hinds, Cooper, Adalel, Appleton, O.Z Gedney, Raco, or approved equal.

Supplemental grounding system

- Furith and intold a supplemental grounding system as halocated on the drawings. Support system with rearmagnetic stainless steel citiz, with tubber grooment. Grounding connectors shall be linned capper vair-asses a triadated on the drawings. Provide stranded or sold bare or installed conductors as indicated.
- Supplemental grounding systems All connections to be made with cad welds, except at equipment use type of the evolable grounding means as required by manufacturer; all ground bans are two that spaced with no ox.
- Slaten ground-bars: In the event of staten ground bars, contact Spirit CM for replacement instruction using threaded rod kits.

Existing Structure:

Estiting exposed wing and all expensed outlier, increptories, whiches, devices, boxes, and other experiment that are not to be utilized in the completed protect that the removed or desempted and capped in the well, celling, of the top as that they are conceeded and sale, well, celling, or floor shall be capped in the well, celling, of the top as the thing they are conceeded and sale, well, celling, or floor shall be capped in the well, celling, and decline the conceeded and sale, well, celling, or floor shall be capped in the decline of the conceeding the conceeded and sale, well, celling, or floor shall be conceeded.

Conduit and Conductor installation:

- Conduits shall be fastened securely in picce with approved non-perfacilled stratile for any experiment. Explosive by the permitted, Cheep-liabor the interior in Explosive devices for districting shall be permitted. Cheep-liabor the interior line shall be the client and strategies on the special shall be shal
 - Conductors shall be puted in accordance with accepted good practice.

| Graphics Legend | | | | | | | hyb hyb |
|-----------------|---|--------------------|-----------------|-------------|-------|--------|---------|
| ชั | lee Bidge: Cable Îray: Waliferiillan: | Fence: | Wood/kon fence: | Lease Area: | Power | Telco: | Hybrid: |

| Acronym Legend | PPC: Power Protection Cabinet | | | | RET: Remote Electrical Tilt | | | | | HFC: Hydrogen Fuel Cell | HSM: Hydrogen Slorage Module | |
|----------------|-------------------------------|---------|-------------------------------|----------------------|-----------------------------|--------|---------------------------|--------------------------------------|-------------|--------------------------|------------------------------|----------|
| | Baltery Backup Unit | Cabinet | Code Division Multiple Access | Concrete Masony Unit | Existing | Ground | Global Positioning System | Healing Ventication Air Conditioning | Hybrid line | Multi Modal Base Station | New | Proposed |
| | 880: | CAB | CDMA: | CME | 諩 | GND | GPS | HVAC | HYB: | MMBS: | Ë | <u>:</u> |





| | _ | | | _ | | | _ |
|---|---|------|---|---------------|----------------|-------------------|-------------|
| | | | | 1005 CO ESY 1 | IOS CO SUMITAL | POSICIO SIGNITIVI | PCC-PORTION |
| | | | | 05/29/2014 | 04/04/14 | 41/8/170 | n4tt |
| Г | Г | П | П | 2 | - | ۰ | Au o |

| 102/42/50 | 05 CD Submittel |
|-----------|-----------------|
| 8 | 1005 |







| | u | |
|---|-----|----------------|
| UNDER THE DIRECTION OF A LICENSED INCYESSIONAL ENCHARRE, TO ALTER THE DOCUMENT. | ı | |
| ×= ' | 1 | |
| Z≌ ' | | 7 |
| 03 | H | _ |
| 92 . | | |
| <≌ . | 1 | |
| A | H | 7 |
| BYCHER DOCUMENT | 1 1 | |
| カヹヺ | | Œ |
| ピスラ・ | | |
| υ¥Ω. | ŀІ | |
| 2 ° X | ŧΙ | н |
| a z = : | | |
| wz. | E 1 | |
| žΩ | | ш |
| ∝¤ | | V. PUUUNIGIGIG |
| 82 | 1 | ю |
| ΣÓ | | |
| ⊃¥ | | |
| | | |


SF35XC001-A The Seminary 6450 CAMDEN STREET OAKLAND, CA 9460S


| \sim | | |
|-----------------|--|--------------|
| GENERAL NOTES 2 | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | SHEET NUMBER |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |


GN-2





















| Sprint : | 12657 Alcosto Bird., Suite 300 San Ramon, CA 94583 | Medial Cerk, CA 16594 | Borges | PROJECT NO. 13065105 | | SF35XC001-A The Seminary ANTENNA SPRING ANTENNA SPRING ANTENNA SPRING SPRI | RF-1 |
|------------|---|--|--|---|---|--|-------------------------------|
| | | | . • | | | | NO SCALE A |
| | | | | | | Specs as provided by Sprint is 61"x12"x4.3" Antenna Wolgitt 36.4 lbs Antenna mounting kit weight 13.2 lbs Field verified (e) antenna rad center: 39'.2" | |
| | | Samsung 37.7713333 -122.1785556 276275 276275 Dutdoor Macro Samsung 0 | Top Hat Top Hat Qty Top Hat Weight ([bs) | Speecas provided by Sprint is 15.03" x 21.26" x 8.03" Weight: 59.5 lbs | (actuated as anterna neight plus 20%) GC to field verify jumper length and quantity | Sector 2 Sector 3 | |
| RFDS Sheet | | Equipment Vendor Lattitude Longitude 11.SITE ID Siterra SR Equipment type Equipment Vendor | UADU 1 3.5" x 17.1" x 15.2" | RRH-V3 3 15.5" x 18.6" x 7.48" 54 Weis 10.3.3 8 Solution derived from existing NA NA NA NA | CB-B01-006 | Sector 1 KNW ET-X-WM-18-GS-8P K1 1 61" x 12" x 4" 36 "11 lb estimate, TBD. 50 310 0 0 | ANTENNA SCHEDULE & PARTS LIST |
| | General Site Information | Site ID STASKCOOT Market SF Bay Region West MLA ATC Structure Type ROOFTOP BTTS Type STANDARD Transmit 2495 Whtz - 2590 Mhz Receive 2495 Whtz - 2590 Mhz | Base Equipment BBU Kit BBU Kit Cty BBU Dimensions Growth Cabinet Growth Cabinet Coverth Cabinet Coverth Cabinet Coverth Cabinet Coverth Cabinet Weight | RF Path Information RRH RRH GLY RRH Dirnensions RRH Weight. Ibs. RRH Mount Weight. Lbs. Power and Fiber Cable Cable Cly Weight per foot. Lbs. Diameter. Inches. | cengan Tr. Coax Jumper Cloy Coax Jumper Length Feet. Coax Jumper Weight Coax Jumper Diameter. Inches AISG Cable Cloy AISG Diameter. Inches AISG Cable length. AISG Cable length. Weight of entire AISG cable. Libs. | Antenna Sector Information Antenna make/model Antenna qty Antenna qty Antenna Upimenisons. Inches Antenna Weight, Lighes Antenna Mounting Kit Weight, Libs. C. Height Antenna Azimuth Antenna Mechanical Downtilt Antenna etilt | ×. |
| | | | | | | | |
| | | | | | | | |








ATTACHMENT A







Sprint

SF35XC001-A The Seminary 6450 Camden Street, Oakland, CA 94605

ForzaTelecom 1330 N Broadway Ste. 202 Walnut Creek, CA 94596 Info@photosims.com



Ü



Sprint

ATTACHMENT B

Sprint Nextel • Base Station No. SF35xcบบา์A 6450 Camden Street • Oakland, California

Statement of Hammett & Edison, Inc., Consulting Engineers

The firm of Hammett & Edison, Inc., Consulting Engineers, has been retained by Sprint Nextel, a personal wireless telecommunications carrier, to evaluate proposed modifications to its existing base station (Site No. SF35xc001A) located at 6450 Camden Street in Oakland, California, for compliance with appropriate guidelines limiting human exposure to radio frequency ("RF") electromagnetic fields.

Executive Summary

Sprint Nextel proposes to install directional panel antennas above the roof of the Evergreen Cemetery building located at 6450 Camden Street in Oakland. The proposed operation will, together with the existing base station at the site, comply with the FCC guidelines limiting public exposure to RF energy.

Prevailing Exposure Standards

The U.S. Congress requires that the Federal Communications Commission ("FCC") evaluate its actions for possible significant impact on the environment. A summary of the FCC's exposure limits is shown in Figure 1. These limits apply for continuous exposures and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health. The most restrictive FCC limit for exposures of unlimited duration to radio frequency energy for several personal wireless services are as follows:

| Wireless Service | Frequency Band | Occupational Limit | Public Limit |
|-----------------------------------|------------------|------------------------|-------------------------|
| Microwave (Point-to-Point) 5 | 5,000–80,000 MHz | 5.00 mW/cm^2 | 1.00 mW/cm ² |
| BRS (Broadband Radio) | 2,600 | 5.00 | 1.00 |
| WCS (Wireless Communication) | 2,300 | 5.00 | 1.00 |
| AWS (Advanced Wireless) | 2,100 | 5.00 | 1.00 |
| PCS (Personal Communication) | 1,950 | 5.00 | 1.00 |
| Cellular | 870 | 2.90 | 0.58 |
| SMR (Specialized Mobile Radio | 855 | 2.85 | 0.57 |
| 700 MHz | 700 | 2.40 | 0.48 |
| [most restrictive frequency range | e] 30–300 | 1.00 | 0.20 |

General Facility Requirements

Base stations typically consist of two distinct parts: the electronic transceivers (also called "radios" or "channels") that are connected to the traditional wired telephone lines, and the passive antennas that send the wireless signals created by the radios out to be received by individual subscriber units. The transceivers are often located at ground level and are connected to the antennas by coaxial cables. A small antenna for reception of GPS signals is also required, mounted with a clear view of the sky. Because of the short wavelength of the frequencies assigned by the FCC for wireless services, the



Sprint Nextel • Base Station No. SF35xc001A 6450 Camden Street • Oakland, California

antennas require line-of-sight paths for their signals to propagate well and so are installed at some height above ground. The antennas are designed to concentrate their energy toward the horizon, with very little energy wasted toward the sky or the ground. This means that it is generally not possible for exposure conditions to approach the maximum permissible exposure limits without being physically very near the antennas.

Computer Modeling Method

The FCC provides direction for determining compliance in its Office of Engineering and Technology Bulletin No. 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radio Frequency Radiation," dated August 1997. Figure 2 attached describes the calculation methodologies, reflecting the facts that a directional antenna's radiation pattern is not fully formed at locations very close by (the "near-field" effect) and that at greater distances the power level from an energy source decreases with the square of the distance from it (the "inverse square law"). The conservative nature of this method for evaluating exposure conditions has been verified by numerous field tests.

Site and Facility Description

Based upon information provided by Sprint Nextel, including construction drawings by Borges Architectural Group, Inc., dated February 18, 2014, that carrier presently has three Andrew directional panel antennas – two Model RR65-18-00DPL2 and one Model RR90-17-00DP – installed behind existing view screens above the roof of the two-story Evergreen Cemetery building located at 6450 Camden Street in Oakland. It is proposed to install three KMW Model ET-X-WM-18-65-8P directional panel antennas next to its existing antennas, mounted with up to 4° downtilt at an effective height of about 39 feet above the ground elevation at the front of the building, 10 feet above the roof, oriented in pairs toward 100°T, 180°T, and 310°T. The maximum effective radiated power in any direction would be 8,250 watts, representing simultaneous operation at 1,560 watts for BRS and 6,690 watts for PCS.

Presently located above the roof of the same building are similar antennas for use by T-Mobile. For the limited purpose of this study, the transmitting facilities of that carrier are assumed to be as follows:

| Service | Maximum ERP | Antenna Model | Downtilt | Height | |
|---------|---------------|---------------------|----------|--------------|--|
| AWS | 4,400 watts) | Ericsson AIR21 | 2° | 39 ft | |
| PCS | 2.200 | E11055011 7 11172 1 | 2 | <i>37</i> 10 | |

Study Results

For a person anywhere at ground, the maximum RF exposure level due to the proposed Sprint Nextel operation by itself is calculated to be 0.038 mW/cm², which is 3.8% of the applicable public exposure



Sprint Nextel • Base Station No. SF35xc001A 6450 Camden Street • Oakland, California

limit. The maximum calculated cumulative level at ground, for the simultaneous operation of both carriers, is 5.3% of the public exposure limit. The maximum calculated cumulative level at any nearby residence* is 5.2% of the public exposure limit. The maximum calculated cumulative level on the roof of the subject building in 87% of the public exposure limit. It should be noted that these results include several "worst-case" assumptions and therefore are expected to overstate actual power density levels.

Recommended Mitigation Measures

Due to their mounting locations, the Sprint Nextel antennas would not be accessible to the general public, and so no mitigation measures are necessary to comply with the FCC public exposure guidelines. To prevent occupational exposures in excess of the FCC guidelines, it is recommended that appropriate RF safety training be provided to all authorized personnel who have access to the antennas, including employees and contractors of the wireless carriers as well as building maintenance staff. No access within 10 feet directly in front of the antennas themselves, such as might occur during maintenance work above the roof, should be allowed while the base station is in operation, unless other measures can be demonstrated to ensure that occupational protection requirements are met. Posting explanatory signs[†] at the roof access hatch, on the screens in front of the antennas, and on the antennas themselves, such that the signs would be readily visible from any angle of approach to persons who might need to work within that distance, would be sufficient to meet FCC-adopted guidelines. Similar measures should already be in place for the other carrier at the site; the applicable keep-back distance for that carrier has not been determined as part of this study.

Conclusion

Based on the information and analysis above, it is the undersigned's professional opinion that the proposed operation of the Sprint Nextel base station located at 6450 Camden Street in Oakland, California, will comply with the prevailing standards for limiting public exposure to radio frequency energy and, therefore, will not for this reason cause a significant impact on the environment. The highest calculated level in publicly accessible areas is much less than the prevailing standards allow for exposures of unlimited duration. This finding is consistent with measurements of actual exposure conditions taken at other operating base stations. Training of authorized personnel and posting explanatory signs is recommended to establish compliance with occupational exposure limitations.

[†] Signs should comply with OET-65 color, symbol, and content recommendations. Contact information should be provided (e.g., a telephone number) to arrange for access to restricted areas. The selection of language(s) is not an engineering matter, and guidance from the landlord, local zoning or health authority, or appropriate professionals may be required.



^{*} Located at least 290 feet away, based on photographs from Google Maps.

Sprint Nextel • Base Station No. SF35xc001A 6450 Camden Street • Oakland, California

Authorship

The undersigned author of this statement is a qualified Professional Engineer, holding California Registration No. E-18063, which expires on June 30, 2015. This work has been carried out under his direction, and all statements are true and correct of his own knowledge except, where noted, when data has been supplied by others, which data he believes to be correct.

No. E-18063 Exp. 6-30-2015

Rajat Mathur, P.E.

707/996-5200


April 21, 2014

FCC Radio Frequency Protection Guide

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The FCC adopted the limits from Report No. 86, "Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," published in 1986 by the Congressionally chartered National Council on Radiation Protection and Measurements ("NCRP"). Separate limits apply for occupational and public exposure conditions, with the latter limits generally five times more restrictive. The more recent standard, developed by the Institute of Electrical and Electronics Engineers and approved as American National Standard ANSI/IEEE C95.1-2006, "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," includes similar limits. These limits apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health.

As shown in the table and chart below, separate limits apply for occupational and public exposure conditions, with the latter limits (in *italics* and/or dashed) up to five times more restrictive:

| <u>Frequency</u> | Electromagnetic Fields (f is frequency of emission in MHz) | | | | | | | |
|------------------------------|--|-----------------|-------------------------------------|----------------|--|-----------|--|--|
| Applicable Range (MHz) | Electric Field Strength (V/m) | | Magnetic Field Strength (A/m) | | Equivalent Far-Field Power Density (mW/cm ²) | | | |
| 0.3 - 1.34 | 614 | 614 | 1.63 | 1.63 | 100 | 100 | | |
| 1.34 - 3.0 | 614 | 823.8/f | 1.63 | 2.19/f | 100 | $180/f^2$ | | |
| 3.0 - 30 | 1842/ f | 823.8/f | 4.89/ f | 2.19/f | 900/ f ² | 180/f² | | |
| 30 - 300 | 61.4 | 27.5 | 0.163 | 0.0729 | 1.0 | 0.2 | | |
| 300 - 1,500 | 3.54 √ f | 1.59 √ f | $\sqrt{f}/106$ | $\sqrt{f/238}$ | f/300 | f/1500 | | |
| 1,500 - 100,000 | 137 | 61.4 | 0.364 | 0.163 | 5.0 | 1.0 | | |



Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits, and higher levels also are allowed for exposures to small areas, such that the spatially averaged levels do not exceed the limits. However, neither of these allowances is incorporated in the conservative calculation formulas in the FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) for projecting field levels. Hammett & Edison has built those formulas into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radio sources. The program allows for the description of buildings and uneven terrain, if required to obtain more accurate projections.



RFR.CALC[™] Calculation Methodology

Assessment by Calculation of Compliance with FCC Exposure Guidelines

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The maximum permissible exposure limits adopted by the FCC (see Figure 1) apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health. Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits.

Near Field.

Prediction methods have been developed for the near field zone of panel (directional) and whip (omnidirectional) antennas, typical at wireless telecommunications base stations, as well as dish (aperture) antennas, typically used for microwave links. The antenna patterns are not fully formed in the near field at these antennas, and the FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) gives suitable formulas for calculating power density within such zones.

For a panel or whip antenna, power density $S = \frac{180}{\theta_{BW}} \times \frac{0.1 \times P_{net}}{\pi \times D \times h}$, in mW/cm²,

and for an aperture antenna, maximum power density $S_{max} = \frac{0.1 \times 16 \times \eta \times P_{net}}{\pi \times h^2}$, in mW/cm²,

where θ_{BW} = half-power beamwidth of the antenna, in degrees, and

 P_{net} = net power input to the antenna, in watts,

D = distance from antenna, in meters,

h = aperture height of the antenna, in meters, and

 η = aperture efficiency (unitless, typically 0.5-0.8).

The factor of 0.1 in the numerators converts to the desired units of power density.

Far Field.

OET-65 gives this formula for calculating power density in the far field of an individual RF source:

power density
$$S = \frac{2.56 \times 1.64 \times 100 \times RFF^2 \times ERP}{4 \times \pi \times D^2}$$
, in mW/cm²,

where ERP = total ERP (all polarizations), in kilowatts,

RFF = relative field factor at the direction to the actual point of calculation, and

D = distance from the center of radiation to the point of calculation, in meters.

The factor of 2.56 accounts for the increase in power density due to ground reflection, assuming a reflection coefficient of 1.6 ($1.6 \times 1.6 = 2.56$). The factor of 1.64 is the gain of a half-wave dipole relative to an isotropic radiator. The factor of 100 in the numerator converts to the desired units of power density. This formula has been built into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radiation sources. The program also allows for the description of uneven terrain in the vicinity, to obtain more accurate projections.

