Case File Number: PLN14155 **November 19, 2014**

5460 Bancroft Avenue (See map on reverse) Location:

Assessors Parcel Numbers: (035-2389-003-00)

To install 3 new antennas and 3 new Remote Radio Heads (RRH's) to

an existing roof top Mini Telecommunications Facility. (associated

equipment cabinets are on the ground floor)

Phil Gamick (for Sprint) Applicant:

Contact Person/Phone same

Proposal:

(530)386-5253 Number:

Owner: Charles H. Joe & Shryel J. Joe by T10 Unison Site Management

LLC, its agent and attorney in fact

Case File Number: PLN14155

Major Conditional Use Permit and Regular Design Review for Mini-**Planning Permits Required:**

telecommunication facility in a residential zone.

Urban Residential and Detached Unit Residential General Plan:

RU-4 Garden Apartment Zone Regulations Zoning:

Environmental Exempt, Section 15301 of the State CEQA Guidelines; minor

additions and alterations to an existing facility **Determination:**

Exempt, Section 15183 of the State CEQA Guidelines; projects

consistent with a community plan, general Plan or zoning.

Survey rating: C3 **Historic Status:**

Service Delivery District: City Council District:

Date Filed: 5/19/14

Finality of Decision: Appealable to City Council within 10 days


Contact case planner Moe Hackett at (510) 238-3973 or

For Further Information: mhackett@oaklandnet.com

SUMMARY

The following staff report addresses the proposal for a new unmanned wireless telecommunication facility located on the roof of an existing multi-family residential building with an associated equipment cabinet located in the ground floor of the building. The project site already contains 3 telecommunication antennas and associated basement located equipment cabinets and this project would add three (3) additional antennas (with new screening) for a total of 6 antennas. Given the number of antennas, this would be considered a "Mini" Telecommunications Facility. The site is a rectangular-shaped with street frontage facing on the two sides (Bancroft Avenue and Cole Street.). The site is in the RU-4 Zone. The General Plan designation for the site is Urban Residential, with the rear of the lot abutting both the CN-3 and Neighborhood Commercial Mixed Use Zone and General Plan. The scope of work entails replacement of the existing screening device for a larger one designed to conceal the 3 reconfigured and 3 additional antennas (six) total, and the new total of 6 RRH's. The proposal would also require the installation of a new equipment cabinet and batteries (that would be located within an existing ground floor Sprit equipment room). The expanded penthouse structure will be located near the building's north side. The building is "U shaped" at this end

CITY OF OAKLAND PLANNING COMMISSION



Case File: PLN14155

Applicant: Sean Snyder / Phil Gamick (for: Sprint)

Address: 5460 Bancroft Avenue

Zone: RU-4

(the rear) and is approximately 10 feet (minimum) from the rear wall of the building. This penthouse expansion will be painted and textured to match the existing screening device and the existing building fenestration (Spanish tile /brick)

TELECOMMUNICATIONS BACKGROUND

Limitations on Local Government Zoning Authority under the Telecommunications Act of 1996

Section 704 of the Telecommunications Act of 1996 (TCA) provides federal standards for the siting of "Personal Wireless Services Facilities." "Personal Wireless Services" include all commercial mobile services (including personal communications services (PCS), cellular radio mobile services, and paging); unlicensed wireless services; and common carrier wireless exchange access services. Under Section 704, local zoning authority over personal wireless services is preserved such that the FCC is prevented from preempting local land use decisions; however, local government zoning decisions are still restricted by several provisions of federal law.

Under Section 253 of the TCA, no state or local regulation or other legal requirement can prohibit or have the effect of prohibiting the ability of any entity to provide any interstate or intrastate telecommunications service.

Further, Section 704 of the TCA imposes limitations on what local and state governments can do. Section 704 prohibits any state and local government action which unreasonably discriminates among personal wireless providers. Local governments must ensure that its wireless ordinance does not contain requirements in the form of regulatory terms or fees which may have the "effect" of prohibiting the placement, construction, or modification of personal wireless services.

Section 704 also preempts any local zoning regulation purporting to regulate the placement, construction and modification of personal wireless service facilities on the basis, either directly or indirectly, on the environmental effects of radio frequency emissions (RF) of such facilities, which otherwise comply with FCC standards in this regard. See, 47 U.S.C. 332(c)(7)(B)(iv) (1996). This means that local authorities may not regulate the siting or construction of personal wireless facilities based on RF standards that are more stringent than those promulgated by the FCC.

Section 704 mandates that local governments act upon personal wireless service facility siting applications to place, construct, or modify a facility within a reasonable time. 47 U.S.C.332(c)(7)(B)(ii). See FCC Shot Clock ruling setting forth "reasonable time" standards for applications deemed complete.

Section 704 also mandates that the FCC provide technical support to local governments in order to encourage them to make property, rights-of-way, and easements under their jurisdiction available for the placement of new spectrum-based telecommunications services. This proceeding is currently at the comment stage.

For more information on the FCC's jurisdiction in this area, contact Steve Markendorff, Chief of the Broadband Branch, Commercial Wireless Division, Wireless Telecommunications Bureau, at (202) 418-0640 or e-mail "smarkend@fcc.gov".

Page 4

Case File Number: PLN14155

PROJECT DESCRIPTION

The applicant (Sprint) is proposing a co-location for the removal and relocation, and addition of what will be a total of 6 antennas with additional rooftop screening. The new portion of the stealth roof-top penthouse structure will be painted and textured to match the existing screen. This entire proposal will be located on roof top of an existing multi-unit residential structure. Through conditions of approval the antennas shall be enclosed and/or painted and textured to match the existing building. The proposal for the equipment cabinet is to locate on the ground floor of the building. All proposed antennas and associated equipment will not be accessible to the public. (See Attachment A).

PROPERTY DESCRIPTION

The subject property is a through lot of approximately 6,000 square feet, with frontage on Bancroft Avenue and Cole Street. The subject property contains a multi-family unit residential facility (apartment building) with a 15-foot setback from the adjacent a lot. Currently there is a Micro Telecommunication facility with a single telecommunication provider (Sprint) on the property including existing screened antennas and equipment cabinets in a portion of the buildings ground floor.

GENERAL PLAN ANALYSIS

The subject property is located within the Urban Residential General Plan designation. The Urban Residential land use classification is intended to identify, create, maintain and enhance an area appropriate for multi-unit, mid-rise, or high-rise residential structures in locations with good access to public transit. The proposed unmanned wireless telecommunication facility will not adversely affect and detract from the residential or commercial characteristics of the neighborhood. The antennas will be mounted on the existing apartment building and visual impacts will be mitigated since the antennas will be enclosed and/or painted and textured to match the existing building. General Plan Policy N9.9 states that the City encourages rehabilitation efforts which respect the architectural integrity of a building's original style. The proposed project will have very minimal effect on the existing building.

ZONING ANALYSIS

The subject property is located within the RU-4 Zone. The RU-4 zone is intended to create, preserve, and enhance areas for single or two-family dwellings and garden apartments in spacious settings usually associated or low to medium residential density. The proposal is for a new unmanned wireless telecommunication facility on an existing Multi-Family Residential Facility and requires a Major Conditional Use Permit since the project is within a residential zone.

This proposal also requires the expansion of the existing roof top screening structure (penthouse) to allow for the new antenna panels. The proposed (expanded) penthouse projection would be 55 feet above ground level, with the tops of the antennas projecting an additional 6 inches to create the appearance of a chimney pipe (and also allowing for a slightly shorter screening device with less visual massing). The structure is 7 feet high (plus 6" for the faux "chimney

pipe" antenna) from the top of the parapet wall and is 55 ½ feet overall above ground level. Chapter 17.128.060A(3) allows for mini facilities to exceed the height limitations above the parapet at any height less than 15 feet.

ENVIRONMENTAL DETERMINATION

The California Environmental Quality Act (CEQA) Guidelines lists the projects that qualify as categorical exemptions from environmental review. The proposed project is categorically exempt from the environmental review requirements pursuant to Section 15301, additions and alterations to existing facilities, and 15183, projects consistent with a community plan, general plan or zoning.

KEY ISSUES AND IMPACTS

1. Conditional Use Permit

Section 17.46.080 of the City of Oakland Planning Code requires a conditional use permit to install or modify an existing Mini Telecommunication facility in the RU-4 zone. Furthermore, Section 17.134.020 of the Planning Code defines such facilities that are in or within 100' of a residential zone as Major Conditional Use Permits and subject to Planning Commission approval.

2. Project Site

Section 17.128.110 of the City of Oakland Telecommunication Regulations indicate that new wireless facilities shall generally be located on designated properties or facilities in the following order of preference:

- A. Co-located on an existing structure or facility with existing wireless antennas.
- B. City owned properties or other public or quasi-public facilities.
- C. Existing commercial or industrial structures in non-residential zones.
- D. Existing commercial or industrial structures in residential zones.
- E. Other non-residential uses in residential zones.
- F. Residential uses in non-residential zones.
- G. Residential uses in residential zones.
- *Facilities locating on an A, B or C ranked preference do not require a site alternatives analysis.

Since the proposed project involves co-locating the installation of new antennas and associated equipment cabinets on an existing facility, the proposed project meets (A) co-locating on an existing structure or facility with existing wireless antennas.

4. Project Design

Section 17.128.120 of the City of Oakland Telecommunications Regulations indicates that new wireless facilities shall generally be designed in the following order of preference:

Case File Number: PLN14155 Page 6

- A. Building or structure mounted antennas completely concealed from view.
- B. Building or structure mounted antennas set back from roof edge, not visible from public right-of way.
- C. Building or structure mounted antennas below roof line (facade mount, pole mount) visible from public right-of-way, painted to match existing structure.
- D. Building or structure mounted antennas above roof line visible from public right of-way.
- E. Monopoles.
- F. Towers.
- * Facilities designed to meet an A or B ranked preference do not require a site design alternatives analysis. Facilities designed to meet a C through F ranked preference, inclusive, must submit a site design alternatives analysis as part of the required application materials. A site design alternatives analysis shall, at a minimum, consist of:
- a. Written evidence indicating why each higher preference design alternative can not be used. Such evidence shall be in sufficient detail that independent verification could be obtained if required by the City of Oakland Zoning Manager. Evidence should indicate if the reason an alternative was rejected was technical (e.g. incorrect height, interference from existing RF sources, inability to cover required area) or for other concerns (e.g. inability to provide utilities, construction or structural impediments).

City of Oakland Planning staff have reviewed and determined that the site selected is conforming to all other telecommunication regulation requirements. The project has met design criteria (A) since the antennas and/or dishes shall be mounted completely concealed behind an enclosure with paint and texture to match the existing building. (Note: the 6" extension of the antennas tops is both intentional and was a design consideration recommended by staff to both reduce the overall massing and height that a fully enclosed screening device would have created, and to create the appearance of a more realistic roof top chimney element which very often include chimney piped protruding above the stack enclosure.) Furthermore, to mitigate visual impacts the antennas will be mounted at approximately the same height and rooftop location above the public right of way. The associated equipment cabinet will have no visual impact since the equipment will be placed in a ground floor existing equipment room.

5. Project Radio Frequency Emissions Standards

Section 17.128.130 of the City of Oakland Telecommunication Regulations require that the applicant submit the following verifications including requests for modifications to existing facilities:

- a. With the initial application, a RF emissions report, prepared by a licensed professional engineer or other expert, indicating that the proposed site will operate within the current acceptable thresholds as established by the Federal government or any such agency who may be subsequently authorized to establish such standards.
- b. Prior to commencement of construction, a RF emissions report indicating the baseline RF emissions condition at the proposed site.

c. Prior to final building permit sign off, an RF emissions report indicating that the site is actually operating within the acceptable thresholds as established by the Federal government or any such agency who may be subsequently authorized to establish such standards.

The applicant states that the proposed project meets the radio frequency (RF) emissions standards as required by the regulatory agency. Submitted with the initial application was a RF emissions report, prepared by EBI Consulting (Attachment B). The report states that the proposed project will comply with the Site Safety Plan for limiting public exposure to radio frequency energy and, therefore, will not cause a significant impact on the environment. Additionally, staff recommends that prior to the final building permit sign off, the applicant submits certified RF emissions report stating that the facility is operating within acceptable thresholds established by the regulatory federal agency.

CONCLUSION

The addition of new antennas to existing Telecommunications facilities is common and such colocation is often encouraged. Staff believes that the findings for approval can be made to support the Conditional Use Permit and Design Review. City of Oakland planning staff recommends the Planning Commission approve the project.

RECOMMENDATIONS:

- 1. Affirm staff's environmental determination and
- 2. Approve Conditional Use Permit, and Design Review application PLN14155 subject to the attached findings and conditions of approval.

Prepared by:

Moe Hackett Planner II

Approved by:

Scott Miller
Zoning Manager

Approved for forwarding to the City Planning Commission

Darin Ranelletti, Deputy Director
Department of Planning and Building

Case File Number: PLN14155

Page 8

ATTACHMENTS:

- A. Project Plans & Photo simulations
- B. Hammett & Edison, INC. Consulting Engineers (Sprint Base Station No. SF36xc032 5460 Bancroft Avenue. Oakland California)

Case File Number: PLN14155 Page 9

FINDINGS FOR APPROVAL

FINDINGS FOR APPROVAL:

This proposal meets all the required findings under Section 17.134.050, of the General Use Permit criteria; all the required findings under Section 17.136.050.(B), of the Non-Residential Design Review criteria; all the required findings under Section 17.128.060(B), of the telecommunication facilities (Mini) Design Review criteria; and all the required findings under Section 17.128.060.(C), of the telecommunication facilities (Mini) Conditional Use Permit criteria; and as set forth below and which are required to approve your application. Required findings are shown in **bold** type; reasons your proposal satisfies them are shown in normal type.

SECTION 17.134.050 – GENERAL USE PERMIT FINDINGS:

A. That the location, size, design, and operating characteristics of the proposed development will be compatible with, and will not adversely affect, the livability or appropriate development of abutting properties and the surrounding neighborhood, with consideration to be given to harmony in scale, bulk, coverage, and density; to the availability of civic facilities and utilities; to harmful effect, if any upon desirable neighborhood character; to the generation of traffic and the capacity of surrounding streets; and to any other relevant impact of the development.

The proposed telecommunications antennas will be co-located within a new penthouse on the roof top of an existing building and will not adversely affect the operating characteristic or livability of the existing area. The facility will be unmanned and will not create additional vehicular traffic in the area. The minor expansion of the existing penthouse screening devices will not create any noticeable or adverse impacts.

B. That the location, design, and site planning of the proposed development will provide a convenient and functional living, working, shopping, or civic environment, and will be as attractive as the nature of the use and its location and setting warrant.

The proposal is a Telecommunications Facility on the roof of a residential building. It meets this finding by co-locating with existing carrier, reducing the need for more telecommunications facilities on other nearby properties. The equipment and antennas have been screened to match the building and such stealthing will help this facility blend in with the building and surroundings and make this facility more attractive than just normal antennas.

C. That the proposed development will enhance the successful operation of the surrounding area in its basic community functions, or will provide an essential service to the community or region.

The proposed development will enhance the successful operation of the surrounding area in its basic community function and will provide an essential service to the community or region. This will be achieved by improving the functional use of the site by providing a regional telecommunication facility for the community and will be available to police, fire, public safety organizations and the general public.

Case File Number: PLN14155

Page 10

D. That the proposal conforms to all applicable design review criteria set forth in the DESIGN REVIEW PROCEDURE of Chapter 17.136 of the Oakland Planning Code.

The proposal conforms with all significant aspects of the design review criteria set forth in Chapter 17.136 of the Oakland Planning Code, as outlined below.

E. That the proposal conforms in all significant respects with the Oakland General Plan and with any other applicable plan or development control map which has been adopted by the City Council.

The proposal conforms in all significant aspects with the Oakland General Plan and with any other applicable plan or zoning maps adopted by the City of Oakland. The proposed minitelecommunication facility in the Urban Residential Use General Plan designation will enhance and improve communication service for a mixture of residential, civic, commercial and institutional uses in the area.

17.136.050(B) - NON-RESIDENTIAL DESIGN REVIEW CRITERIA:

1. That the proposal will help achieve or maintain a group of facilities which are well related to one another and which, when taken together, will result in a well-composed design, with consideration given to site, landscape, bulk, height, arrangement, texture, materials, colors, and appurtenances; the relation of these factors to other facilities in the vicinity; and the relation of the proposal to the total setting as seen from key points in the surrounding area. Only elements of design which have some significant relationship to outside appearance shall be considered, except as otherwise provided in Section 17.136.060;

The proposal is the addition to a mini telecommunications facility which includes the addition of three (3) new panel antennas and removal and relocation of three (3) other antennas within an expanded penthouses at the roof of the existing building and one equipment cabinet located within an existing ground floor equipment room. The proposed antennas are consistent and well related to the surrounding area in scale, bulk, height, materials, and textures. The antennas will also be located approximately 55 feet 6 inches above, and 17 feet (approximate) away from the public right of way (the Cole Street Edge of the building).

2. That the proposed design will be of a quality and character which harmonizes with, and serves to protect the value of, private and public investments in the area;

The design will be appropriate and compatible with current zoning and general plan land use designations. The proposal protects and preserves the surrounding neighborhood context by adding additional wireless telecommunication antennas to a commercial and residential area. The antennas will be concealed and disguised from public view and will not have any visual impact on the neighborhood.

3. That the proposed design conforms in all significant respects with the Oakland General Plan and with any applicable design review guidelines or criteria, district plan, or

Case File Number: PLN14155 Page 11

development control map which have been adopted by the Planning Commission or City Council.

The proposal conforms with the City of Oakland Comprehensive General Plan meeting specific General Plan policies and the Supplemental Report and Recommendations on Revisions to the Citywide Telecommunications Regulations. The proposal will conform to performance standards for noise set forth in Section 17.120.050 for decibels levels in residential areas for both day and nighttime use. The Project conforms to all macro-facility definitions set forth in Section 17.128.070 and meets all design review criteria to minimize all impacts throughout the neighborhood

17.128.060(B) DESIGN REVIEW CRITERIA FOR MINI FACILITIES

1. Antennas should be painted and/or textured to match the existing structure:

The proposed antennas will be completely concealed from public view behind a screening enclosure and/or painted and textured to match the existing structure and located at the roof top of an existing building. (In this case the colors will match the color of the buildings Spanish tile elements, and a grey or brown tone for the appearance of a chimney pipe.)

2. Antennas mounted on architecturally significant structures or significant architectural details of the building should be covered by appropriate casings which are manufactured to match existing architectural features found on the building:

The addition of the antennas and RRH's to the existing building will be mounted behind screening enclosure on the roof with the size, placement, configuration, materials, texture, and color to be submitted to the Planning and Zoning division for review and approval prior to the issuance of a building permit.

3. Where feasible, antennas can be placed directly above, below or incorporated with vertical design elements of a building to help in camouflaging:

The proposed antennas shall be mounted behind enclosures with the size, placement, configuration, materials, texture, and color to be submitted to the Planning and Zoning division for review and approval prior to the issuance of a building permit. The cable trays shall be painted to match the color of the building.

4. Equipment shelters or cabinets shall be concealed from view or placed underground:

The equipment will be within the building in an existing ground floor Sprint equipment room and will not be visible from the street.

5. That all reasonable means of reducing public access to the antennas and equipment has been made, including, but not limited to, placement in or on buildings or structures, fencing, anti-climbing measures and anti-tampering devices.

Case File Number: PLN14155

Page 12

The antennas will be mounted to the roof and will not be accessible to the public due to its location. The equipment will be located with the building in a dedicated equipment room and will not be visible or accessible to the public.

6. For antennas attached to the roof, maintain a 1:1 ratio for equipment setback; screen the antennas to match existing air conditioning units, stairs, or elevator towers; avoid placing roof mounted antennas in direct line with significant view corridors.

The proposed antennas and RRH's will be co-located on the roof top in a existing and (slightly) expanded penthouses designed to screen the facilities. The penthouse location will not be altered on the building's roof and shall be textured and painted to match the existing building. The new equipment screen achieves a greater than 1:1 ratio at no more than 7 ½ feet height over the lowest rooftop parapet wall edge. Due to the shape of the building, and the height and stealth design characteristics the proposal will not alter or degrade sight lines or view corridors.

Section 17.128.060(C) CONDITIONAL USE PERMIT (CUP) FINDINGS FOR MINI FACILITIES

1. The project must meet the special design review criteria listed in subsection B of this section (17.128.060B):

The proposed project meets the special design review criteria listed in section 17.128.060B.

2. The proposed project must not disrupt the overall community character:

Due to the proposed project co-locating with other existing telecommunication antennas and equipment, it will not disrupt the overall community character of the site.

Case File Number: PLN14155

Page 13

CONDITIONS OF APPROVAL PLN14155

STANDARD CONDITIONS:

1. Approved Use

Ongoing

- a) The project shall be constructed and operated in accordance with the authorized use as described in the application materials, PLN14155, and the revised plans submitted on **September 26, 2014** and as amended by the following conditions. Any additional uses or facilities other than those approved with this permit, as described in the project description and the approved plans, will require a separate application and approval. Any deviation from the approved drawings, Conditions of Approval or use shall required prior written approval from the Director of City Planning or designee.
- b) This action by the City Planning Commission ("this Approval") includes the approvals set forth below. This Approval includes: The installation of a mini telecommunications facility located on the roof of an existing building at 5460 Bancroft Avenue (APN: 035-2389-003-00), under Oakland Municipal Code 17.128, 17.136 and 17.134.

2. Effective Date, Expiration, Extensions and Extinguishment Ongoing

Unless a different termination date is prescribed, this Approval shall expire **two calendar years** from the approval date, unless within such period all necessary permits for construction or alteration have been issued, or the authorized activities have commenced in the case of a permit not involving construction or alteration. Upon written request and payment of appropriate fees submitted no later than the expiration date of this permit, the Director of City Planning or designee may grant a one-year extension of this date, with additional extensions subject to approval by the approving body. Expiration of any necessary building permit for this project may invalidate this Approval if the said extension period has also expired.

3. Scope of This Approval; Major and Minor Changes

Ongoing

The project is approved pursuant to the **Planning Code** only. Minor changes to approved plans may be approved administratively by the Director of City Planning or designee. Major changes to the approved plans shall be reviewed by the Director of City Planning or designee to determine whether such changes require submittal and approval of a revision to the approved project by the approving body or a new, completely independent permit.

4. Conformance with other Requirements

Prior to issuance of a demolition, grading, P-job, or other construction related permit

a) The project applicant shall comply with all other applicable federal, state, regional and/or local laws/codes, requirements, regulations, and guidelines, including but not limited to those imposed by the City's Building Services Division, the City's Fire Marshal, and the City's Public Works Agency. Compliance with other applicable requirements may require changes

Page 14

to the approved use and/or plans. These changes shall be processed in accordance with the procedures contained in Condition of Approval #3.

b) The applicant shall submit approved building plans for project-specific needs related to fire protection to the Fire Services Division for review and approval, including, but not limited to automatic extinguishing systems, water supply improvements and hydrants, fire department access, elevated walking pathways, safety railings, emergency access and lighting.

5. <u>Conformance to Approved Plans; Modification of Conditions or Revocation</u> *Ongoing*

- a) Site shall be kept in a blight/nuisance-free condition. Any existing blight or nuisance shall be abated within 60-90 days of approval, unless an earlier date is specified elsewhere.
- b) Violation of any term, Conditions of Approval or project description relating to the Conditions of Approval is unlawful, prohibited, and a violation of the Oakland Municipal Code. The City of Oakland reserves the right to initiate civil and/or criminal enforcement and/or abatement proceedings, or after notice and public hearing, to revoke the Approvals or alter these conditions of approval if it is found that there is violation of any of the Conditions of Approval or the provisions of the Planning Code or Municipal Code, or the project operates as or causes a public nuisance. This provision is not intended to, nor does it, limit in any manner whatsoever the ability of the City to take appropriate enforcement actions. The project applicant shall be responsible for paying fees in accordance with the City's Master Fee Schedule for inspections conducted by the City or a City-designated third-party to investigate alleged violations of the Conditions of Approval.

6. Signed Copy of the Conditions of Approval

Ongoing

A copy of the approval letter and **Conditions of Approval** shall be signed by the property owner, notarized, and submitted with each set of permit plans to the appropriate City agency for this project.

7. Indemnification

Ongoing

- a) To the maximum extent permitted by law, the applicant shall defend (with counsel acceptable to the City), indemnify, and hold harmless the City of Oakland, the Oakland City Council, the City of Oakland Redevelopment Agency, the Oakland City Planning Commission and its respective agents, officers, and employees (hereafter collectively called City) from any liability, damages, claim, judgment, loss (direct or indirect)action, causes of action, or proceeding (including legal costs, attorneys' fees, expert witness or consultant fees, City Attorney or staff time, expenses or costs) (collectively called "Action") against the City to attack, set aside, void or annul, (1) an approval by the City relating to a development-related application or subdivision or (2) implementation of an approved development-related project. The City may elect, in its sole discretion, to participate in the defense of said Action and the applicant shall reimburse the City for its reasonable legal costs and attorneys' fees.
- b) Within ten (10) calendar days of the filing of any Action as specified in subsection A above, the applicant shall execute a Letter of Agreement with the City, acceptable to the

Case File Number: PLN14155

Page 15

Office of the City Attorney, which memorializes the above obligations. These obligations and the Letter of Agreement shall survive termination, extinguishment or invalidation of the approval. Failure to timely execute the Letter of Agreement does not relieve the applicant of any of the obligations contained in this condition or other requirements or Conditions of Approval that may be imposed by the City.

8. Compliance with Conditions of Approval

Ongoing

The project applicant shall be responsible for compliance with the recommendations in any submitted and approved technical report and all the Conditions of Approval set forth below at its sole cost and expense, and subject to review and approval of the City of Oakland.

9. Severability

Ongoing

Approval of the project would not have been granted but for the applicability and validity of each and every one of the specified Conditions of Approval, and if one or more of such Conditions of Approval is found to be invalid by a court of competent jurisdiction, this Approval would not have been granted without requiring other valid Conditions of Approval consistent with achieving the same purpose and intent of such Approval.

10. Landscape Maintenance.

Ongoing

All new landscaping shall be permanently maintained in good growing condition and, whenever necessary, replaced with new plant materials to ensure continued compliance with applicable landscaping requirements.

11. Operational Noise-General

Ongoing.

Noise levels from the activity, property, or any mechanical equipment on site shall comply with the performance standards of Section 17.120 of the Oakland Planning Code and Section 8.18 of the Oakland Municipal Code. If noise levels exceed these standards, the activity causing the noise shall be abated until appropriate noise reduction measures have been installed and compliance verified by the Planning and Zoning Division and Building Services.

PROJECT SPECIFIC CONDITIONS FOR TELECOMMUNICATIONS FACILITIES

12. Emissions Report

Prior to a final inspection

The applicant shall provide an RF emissions report to the City of Oakland Zoning Division indicating that the site is actually operating within the acceptable thresholds as established by the Federal government or any such agency that may be subsequently authorized to establish such standards.

13. Camouflaging

Prior to building permit approval and ongoing

Plans and paint color samples shall be provided to Zoning during the building permit process to show the final color of all apparatus (including but not limited to antennas, screens, and

Case File Number: PLN14155

Page 16

equipment). The selected paints shall consist of matte or non-reflective colors to match existing finishes. The final color of the antennas and screening device (penthouse /chimney) shall be partly or wholly repainted at the discretion of the Zoning Manager in order to achieve the intended appearance of a chimney with the actual antennas camouflaged to resemble smoke pipes above the screen.

APPROVED BY:			
City Planning Commission:		(date)	(vote)
City Council:	(date)		(vote)

SEP 26 2014

Planning & Zoning Division City of Dakland

PROJECT NAME:

2.5 EQUIPMENT DEPLOYMENT

MELROSE PLACE

SITE NAME:

CASCADE #:

SF36XC032-B

SITE ADDRESS:

5460 BANCROFT AVENUE OAKLAND, CA 94601

ROOFTOP

SITE TYPE:

			SITE / SITE					・ 一般のでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「大きなでは、「				No. 20 Control of the								VICINITY MAP
	II) 2012 NFFA (0), LIFE SAFETY CODE 12) 2013 NFFA 72, NATIONAL FIRE ALARM CODE	III ANNI ENTINEZZAGO			 Ø) 2013 CALFORNIA ÉLECTRICAL CODE (CEC) WITH CALFORNIA AMENDMENTS, BASED ON THE 2011 NEC (PART 3) 	 ZOID CALEORNIA PLUMBING CODE (CPC), BASED ON THE 2012 UPC (PART 5) 	4) 2013 CALFORNIA NECHANICAL CODE (CMC), BASED ON THE 2012 UMC (PART 4)	AMERICANING (FAMILY)	3) 2013 CALFORNIA FIRE CODE (CFC), BASED ON THE 2012 IFC, WITH CALFORNIA	(AFFECIED ENERGY PROVINCING ONCT) - AFFER JULY 1, 2014	4) 2013 CALIFORNIA GREEN BLIEDINGS STANDARDS CODE [CALGREBA] (PART 11)	ON THE ZOIZ IRC (PART 2.5)	3) 2013 CALKORNIA RESIDENTIAL CODE (CRC) WITH APPENDIX IL PATRO COVERS, BASED	THE 2012 BC (PART 2 VOL 1-2)	20 CALEORNIA BIRIDAG CODE ICACI WITH CALEORNIA AMENDACATE SASETI ON	 2013 CALKORNIA ADMAISTRATIVE CODE, CHAPTER 10, PART 1, TITLE 24 CODE OF REGULATIONS- AFTER JULY 1, 2014 	CONFORMING TO THESE CODES.	ALL PORNATION MAILTAINS SHAPE FOLLOWING CODES AS ADOPTIVED BY THE LOCAL GOVERNING MITHOUTHER NOTHING IN THESE PLANS KID BE COLUMNING TO THE WORK AND THE PORT OF T	11 U/O DV 1-17	APPLICABLE CODES
	G-22	9		T		7	A-5	A-4	A-3.2	A-3.1	A-2.2	A-21	1-A		GN-2	Q.	I	Ė	STEEL NO.	
	GROUNDING DETAILS	GROUNDING PLAN & NOTES		SINGLE LINE DIAGRAM & POWER PANEL SCHEDULE		ANTENNA SCHEDULE & PARTS LIST	STEALTH DETAILS	EQUIPMENT DETAILS	ELEVATIONS	ELEVATIONS	ENLARGED ANTENNA PLANS	ENLARGED EQUIPMENT PLANS	OVERALL SITE PLANS		GENERAL NOTES 2	GENERAL NOTES I	TITLE SHEET & PROJECT DATA		SHEET TITLE	DRAWING INDEX
Day's and and and and a	09/00/14		ver contractor	2	O GIZENIA DECOMENDA	+-	3 09/03/14 b00K 03/9/189/2						CHECKED BY: B.K.W.	DRAWNBY: HUH	ı	PROJECT NO: 13065-108		194 M	147811013	Borges

Site Address: 5460 Bancroff Avenue Oakland, CA 94601

SITE INFORMATION

Property Owner: Charles H. Joe & Sheeyt H. Joe 20923 Foothill Blvd Hayward, CA 94541

Sairi Construction Manager, Spiri 1267 Acosta Bed, Sulle 300 San Ramon, Ca 9450 San Ramon, Ca 9450 Confact: tony Pho ph; [415] 264-971 armat: Neison, Pho@sprint.com

ACCESSIBILITY REQUIREMENTS

ACCESSIBILITY

ACCESSIBILITY REQUIREMENTS

ACCESSIBILITY REQUIREMENTS

ACCESSIBILITY REQUIREMENTS

ACCESSIBILITY REQUIREMENTS

ACCESSIBILITY R

SITE

DRIVING DIRECTIONS FROM SPRINT, 12657 ALCOSTA BLVD SAN RAMON, CA

RF ENGINEER-SPRINT SITE ACQUISITION SPRINT CONSTRUCTION-

SF36XC032-B

5460 BANCROFF AVENUE OAKLAND, CA 94601 MELROSE PLACE

TITLE SHEET & PROJECT DATA

ユ

DESTRUCTION WILL BE ON THE RIGHT

SPECIAL INSPECTIONS

37-46 19:2426 N 37-772012

Zoning Julistiction: Alamede County

longlhide [NAD83]; -122* 11" 55.5612" W -122,198767

Zoning District: CC-2

LOCATION MAP

PROJECT DESCRIPTION

SITE ACQUISITION MANAGER-SITE ACQUISITION PLANNER-

APPROVALS

DATE

ATTACHMENT

These outline specifications in conjunction with the sprint standard construction specifications, including contract documents and the construction drawings describe the wark to be performed by the contractor.

section 01 100 - Scope of Work

the Wate: Strall compty with applicable national codes and standards, latest edition, and poritions thereof.

Precedent School selections to the foreign continuelon specifications for wieless sites including the standard continuelon drowing, triannation on the standard continuelon drowing, triannation on the continuelon drowing, shall take precedence.

Sile Familianh; Contractor shall be responsible for familianing hinself with all contract documents, field conditions and dimensions prior to praceeding with construction. <u>Documentations and supervise and direct the work and shall be responsible for contruction means, the control shall supervise and direct the work and shall be recordance with the contract documents. The following the supervises, and proceedures in accordance with the contract documents.</u>

Dewings, Specifications and details required at lobalite; more construction dowings at the jobsile from mebilitations through constitution completion completion and policy from the construction completion completion.

- Dotals are intanded to show design intent, provide all malerials and labor as required to provide a complete and that laboraling system. Modifications may be experted to still job dimensions or considions, and such modifications shall be included as part of the work.
- Contractor that notify spaint construction manager of any variations prior to proceeding with the work-dimensions shown are to finish surfaces unless model otherwise. Modifications may be required to sail job almentions or conditions, and such modifications that he included as part of the was.
- Mark the field set of drawings in red, documenting any changes from the construction documents.

Methods of Procedure (MOPs) for construction: Confractor shall perform work as described in the following installation and commissioning maps.

No pulsal was cachier in the pulsa was cachier in the pulsa was exactly and in the pulsa was performed to be absent used in the pulsa person with prefer double in tradellion or behind cache
in tradellion or RRH: on the pulsa person of RRH: on the pulsa p ∢ ≒ ひ ひ ≡ ≒ ら ≒ ≒ →

Section 01 200 - Company fumished material and equipment

Company furnished material and equipment is identified on the RF data sheet in the construction drawings.

Contractor is responsible for Spirit provided material and equipment to ensure if is protected and handled property throughout the construction duration.

Contractor responsible for receipt of Sprint furnished equipment at cell site or contractors location. Contractor to complete shipping and receipt documentation in accordance with company practice.

Section 01 300 - Cell Site Construction Co.

<u>valice to Proceed:</u> No work strali commence prior to company's written nalice to proceed and the issuance of wark arder.

Sale Clearines and keep the site free from accumulating weate material, debtis, and frost. At the completion of the wast, controlled is also from the site free from the site of remaining tabbish, implements, temporary tradities, and suppla materials.

Section 01 400 - Submittals & Tests

Alteración de la companyat requet, any alteraciónes to the materials or methods precifica that be submitted to Striht controction manager for approvat. Sprin vill review and approve any those requests made in willing. No vertad approvats will be considered.

Tests and Inspections:

The contractor shall be responsible for all construction tests, inspections and project documentation.

Contractor shall accomplish testing including but not limited to the following:

Coax Sweeps and Fiber tests per TS-0200 Rev 4 antenna line acceptance standards.

Aq. azinuth and downfill provide an automated report uploaded to Steria using a commercial mode/act his purpose electrions. Anteriar adjument Tool (AAI): Installed azinuth, centerline and downfill trust conform with RF configuration data

Contractor shall be responsible for any and all corrections to any work identified as unacceptable in site impection activities and/or as a result of testing.

4. All testing required by applicable installation maps.

Required closeout documentation includes, but is not limited to the following:

Azimuth, downtill, AGL from sunsight instruments - Antenna Asgnment Tool (AAT) Sweep and Fiber fests Scanable barcade photographs of tower tap and inaccessible serialized equipment

All available jurisdictional information

PDF scan of redlines produced in field

A PDF scan of redline mark-ups suitable for use in electronic As-Buill drawing production Lien waivers

final payment application

Required final construction photos

Construction and commissioning checklist complete with no deficient items ĕ

All post NIP tasks including document uploads completed in Siterra (Sprint's document repository of record).

Closeout photographs:

a Provide photographs of final project per the following list. Additional photographs may be required to suppart acceptance processes

Back main hybrid cable route (minimum two photos)

Of each antenna and RRH

(iii) Manufacturer's name tag for all serialized equipment

Pull and distribution baxes intermediate between RRH's and MM8S (door open) Ξ

(v) MMBS Cabinet with door open showing modifications (vi) Power cabinet, doors apen, batteries installed

(vii) Break out cylinders

(VIII) ASR Signage for Sprint owned towers

(ix) Radiation exposure warning signs

(x) Photograph from each sector from approximately RAD center of any new antenna at hoizon.

Load photo I o'Stera project Bray IS, In S create new category, 2.5 Deployment, and section; Permanent Construction, Label photos with site cascade and view being depicted. Connecta used to rides photographs shall off 5°s enabled such that the GPS coordinates are included in the photo medicale information.

Commissioning: Perform all commissioning as required by applicable MOPs

Integration: Perform all integration activities as required by applicable MOPs

Section 09 900 - Painting

Quality Assurance:

Comply with governing codes and regulations. Provide products of acceptable manufactures which have been in sudiaction you in similar service for livee years. Use experiented triatiliers. Defert, handle, and store motients in accordance with manufacturer's instructions.

Comply with all environmental regulations for volatile organic compounds.

Materials:

A. Manufacturers: Benjamin Moore, Ici Devoe coatings, PPG, Shewin Williams or approved equal. Provide premium grade, professional-quality products for coating systems

Estator antennoa and antenna mounting backware: One coal of primer and two firths acasts, Paint for estatorate stalle be remortalic backer doctoration mentalic proteines, through estatora and aptients as required to make appearance of antennoa on adjacent buding sunfaces and as acceptable to the owner. Refer to antenno manufactures's instructions whenever possible. Paint Schedule:

Water Tanks: Touch up - prepare surfaces to be repaired. Follow industry standards and requirements of owner to match existing coaling and finish.

ainting Application:

Inspect surfaces, report unsatisfactory conditions in writing; beginning work means acceptance of substrate.

Sprint

12657 Alcosta Blvd., Suite 300 San Ramon, CA 94583

1330 North Broadway Suite 202 Wahrut Creek, CA 94596

Comply with manufacturer's instructions and recommendations for preparation, prinning and coating work. Coordinate with wark of other sections.

Match approved mack-ups for color, texture, and pattern. Re-coat or remove and replace work which does not match as shows lass of achesion.

Clean up, touch up and protect work.

Touchup Painting:

Galvaniaing damage and all botts and nuts shall be touched up after tower erection with "Galvanox," "Dry Galv," or "Zinc-II."

 All metal components shall be handled with care to prevent damage to the components, their preservative treatment, at their protective coalings. 2. Feld touchup paint shall be done in accordance with the manufacturer's written instructions.

Section 11 700 - Antenna assembly, Remote Radio Units and cable installation

<u>Summany:</u> This section specifies installation of antennas, RRHs, and cable equipment, installation, and testing of cooxidist fleet cable.

Antenna, and RRHY; The rumber and type of antenna; and RRHY to be installed is detailed on the construction drawings.

While Cable Wile Bo DC/More and fundined for installation of each site. Cable shall be installed per the construction drowings and the applicable manufacture's requirements.

Borges Borges

PROJECT NO: 13065-108
DRAWN BY: HILH

B.K.W.

CHECKED BY:

Langes and Cornection:
The Appear and Cornection:
The Appear and Total Total Cornection:
The TRACK And Total Cornection:
The TRACK And Total And Total Cornection and Total Corne

insert spec Remote Electrical Tilt (RET) cables:

Miscellaneous; Install splitters, combiners, filters per RF dala sheel, furnished by Sprint.

Adenne insignities.

The controls and assemble at onternas enale in accordance with the instructions supplied by the manufactures that assemble subject, azimuth, and lesed otheritation bloomalion should be a designated on the construction design.

The contractor shall position the antenna on lower pipe mounts so that the bottom strut is level. The pipe mounts shall be plumb to within 1 degree.

1 09/00/14 105/00/28/27/2 2 04/24/14 105/00/28/27/2 1 02/09/14 105/00/28/20/2 0 01/29/14 95/00/28/27/2

DAYCO'14 IOOS. CO SUB REV 2

Anterna mounting requirements: Provide antenna mounting hardware as indicated on the drawings.

Hybrid Cables installation:

A. The contractor shall nowe, test, and install all cables as indicated on the construction drawings and in accordance with the manufacturer's recommendations.

The installed radius of the cables shall not be less than the manufacturer's specifications for bending radii.

C. Extreme care shall be taken to avaid damage to the cables during handling and installation.

Fostening main hybrid cobles: All cables shall be permanently fastened to the coax tadder at 4:0" oc using non-magnetic staintess steel citips.

Fastening individual fiber and DC cables above breakaut enclosure (medusa), within the MMBS cabinel and any intermediate distribution boxes;

Reer: Support Reer bundles using ½" velcros strops of the required length ® 18" ac. Strops shall be UV, oil and water resistant and sullable for industrial installations as manufactured by Taxiol or approved equal.

SF36XC032-B MELROSE PLACE 5460 BANCROFT AVENUE OAKLAND, CA 94601

DC: Support DC bundles with zip lies of the adequate length. Zip lies to be UV stabilized, black nylon, with tensile strength at 12,000 psi as manufactured by Nelco products as equal.

Fastening jumpers. Secure jumpers to the side arms or head frames using stainless steel tie wraps or stainless steel butterfly alips.

Cable installation:

Inspect cable prior to use for shipping damage, notify the construction manager.

Cable rouling: Cable installation shall be planned to ensure that the lines will be properly routed in the cable envelop as indicated on the drawings. Avoid twisting and crossovers.

Hoist cable using proper haisting gips. Do not exceed manufactures recommended maximum bend radius.

GN-1

GENERAL NOTES 1

Continue from GN-1

- Grounding of transmission lines: All transmission lines shall be grounded as indicated on drawings
- Hybrid Cable color coding: All color coding shall be as required in TS 0200 Rev 4.
- Hybid Cable tabeling: Individual Hybrid and DC bundles shall be labeled alpha-numerically according to Sprint cell site engineering notice EN 2012-201, Rev 1

Weatherproofing exterior connectors and hybrid cable ground kits:

- A. All fiber & coax connectors and ground kits shall be weatherproofed.
- Weatherproofed using one of the following methods. All installations must be done in accordance with the manufacturer's recommendations and industry best practices.
- Cold Shirik: Encompass connector in cold shirik tubing and provide a double wrap of 2* electrical tape extending 2* beyond tubing. Provide 3m cold shirik CXS series or equal.
- sel-amalgamaling lape: Cean urlaces, Apply a double wap of sel-amalgamaling lape 2" beyond connector, Apply a second wrap of sel-amalgamaling lape in appoils direction. Apply double woop of 2" wide electrical lape extending 2" beyond the self-amalgamaling lape.
- 3m slim lock closure 716: Substitutions will not be allowed.
- Open flame on job site is not acceptable

Section 11 800 - Installation of Multimodal Base Stations (MMBS) and related equipment

summary:

- This section specifies MMS cabinets, power cabinets, and internal equipment including by not finited to rectifient, power distribution units, base band units, urge arrestors, batteries, and similar equipment furnished by the company for installation by the contractor (OFCI).
- Contracter shall provide and intral districted are materials and provide all labor required for intrallating equipment in existing cabbinet or new cabinet as shown on drawings and as required by the applicable installation maps.
- Comply with manufacturers installation and start-up requirements

DC Circuit Breaker labeling

A. Label circuit breakers according to Sprint cell site engineering notice - EN 2012-001, Rev 1.

Section 26 100 - Basic electrical requirements

Summany: This section specifies basic electrical requirements for systems and component

Quality Assurance:

- A. All equipment furnished under division 26 shall carry UL labels and Islings where such labels and Islings are available in the industry.
- Manufacturers of equipment shall have a minimum of three years experience with their equipment installed and operating in the field in a use similar to the proposed use for this project.
- C. <u>Materials and equipment</u>: All materials and equipment specified in Division 26 of the same type shall
 be of the same manufacturer and shall be new, of the best quality and design, and free from defect

Supporting Devices:

- All equipment furnished under Division 26 shall carry UL labels and listings where such labels and listings are available in the industry.
- Manufacturers of equipment shall have a minimum of three years experience with their equipment installed and operating in the field in a use similar to the proposed use for this project.
- Materials and equipment:
 Materials and equipment is
 Materials and equipment is
 manufacturer and shall be now, of the best quality and design, and free from defects

Supporting Devices:

- Manufactured structural support products by the following: materials: Subject to campliance with requirements, provide
- Allied Tube and Conduit
- B-Line system
- 3. Sunistrut Diversified Products
- 4. Thomas & Belts
- Fasteness: Types, materials, and construction features as follows: Expansion anchors: Carbon steel wedge or steeve type.
- Power-driven threaded studs: Heat-treated steel, designed specifically for the intended service.
- fasten by means of wood screws on wood.
- Toggle bolts on hollow masonsy units.
- Concrete inserts or expansion bolts on concrete or solid masonry
- Machine screws, welded threaded studs, or spring-tension clamps on steet
- Explosive devices for attaching hangers to structure shall not be permitted.
- 8. Do not weld conduit, pipe straps, or items other than threaded studs to steel structures.
- 9. In partitions of light steel construction, use sheet metal screws.

Supporting Devices:

- install supporting devices to fasten electrical components securely and permanently in accordance with NEC.
- Coordinate with the building structural system and with other trades.
- Unless otherwise indicated on the drawings, fasten electrical items and their supporting hardware securely to the structure in accordance with the following:
- Ensure that the load applied by any fastener does not exceed 25 percent of the proof lest load.
- E. Use vibration and shock-resistant fasteness for attachments to concrete slabs.

Electrical Identification:

- Update and provide typed circuit breaker schedules in the mounling bracket, inside doors of AC panel boards with any changes made to the AC system.
- Branch circuits feeding aviation obstruction lighting equipment shall be clearly identified as such at the branch circuit panelboard.

Section 26 200 - Electrical materials and equipment

Conduit:

- (Rigid gehorated steel (Rigid) conduit shall be used for exterior localisms above ground and in unfinited interior locations and for exceeded unit in contrasts. Rigid conduit and litting shall be steel, coasid with size exterior and interior by the hot dip optionalizing process. Conduit shall be produced to Akti specifications (Rigid, in deteral specification) WWA-Ckill and that lies there with the underwinder laborationist. Billings shall be threaded : set sown or compression filtings will not be acceptable. Risk consolution strate for manufactured by Akting-Risk pilot on Whendland.
- Underground conduit in concete shall be Polyrinylchoide (PVC) suitable for direct burial as applicable. Joint shall be belied, and flush solvent welded in accordance with manufacturest instructions. Conduit shall be Calinn etectrical products or approved equal.
- Transitions between PVC and rigid (RGS) shall be made with PVC coaled metallic long sweep radius aboves.
- BM or rigid polyamizad sited candull may be used in fiethed spaces concealed in walls and ceilings. BM shall be mild stee, it estimates when the steep control of the dispending polyamized and produced its ANSI specification (2013, feeters specification WWC-SAS) and shall be full lated. BM shall be marufactured by Alfact, Republic or Wheelband, or approved equal. Filtings shall be melatic compression, set score connections shall not be acceptionbe.
- Liquid light leable metallic conclui shall-be used for find connection to equipment. Rillings shall be metallic glord type compression fillings, maniforting the heapily of concluid pytem. Set screw connections that find the conseptable. Maximum length of leable conduit shall not exceed 6-feet. IFMC shall be protected and supposted carequie by NEC. Manufactures of leable conduit shall be Carol, Arabanda Metal fisses or threated whetal fisses, or approved requir.
- Minimum size conduit shall be 3/4 inch (21mm).

Hubs and Boxes:

- A. Al enticaces to activities or other equipment not howing integral theoded has provide metallic threaded has at of the size and configuration negatived hat shall include lockurul and neoprene o-ring seal. Provide impact resistant 105 degree a plastic bushings to protect cable insudation.
- B. Cable termination fittings for conduit
- Cable terminators for RGS conduits shall be type CRC by O-Z/Gedney or equal.
- 2. Cable terminators for LFMC shall be Etco CL2075; or made for the purpose products by Roxlec

- Conduit outlet bodies shall be plated cast alloy with similar gasketed covers. Outlet bodies shall be of the configuration and size suitable for the application. Provide crouse-tands form 8 or equal.

Supplemental grounding system

- Furth and intall a supplemental grounding system as indicated on the drowings. Support system with non-nagretic staties steel cips with tubber grammets. Grounding connectors shall be timed cappe wite, sizes as indicated on the drawings. Provide stranded or solid bare or haudred conductors as indicated.
- Supplemental granding system: All connections to be made with card welds, except at equipment use lugs or other available grounding means as required by manufacturer; all ground bars use two hole spades with no as.
- Stolen ground-bass in the event of stolen ground bass, contact Spirit CM for replacement instruction using threaded rod kits.

Existing Structure:

Esting exposed witing and all exposed cultels, neepbodes, whiches, devices, boses, and other
explorment that are not to be tilized in the completed project shall be removed at denergized and
capped in the wall, ceiting, of floor so that they are concealed and safe, wall, esting, or floor shall be
packed to match the adjacent continuation.

Conduit and Conductor installation:

- A. Condult shall be fastered securely in place with approved non-periorated attacps and hangest. Explained exhibites the cital chaining hanges to studius will not be permitted. Claely inflow the first of the structure, markinin claes proximity to the structure and teep condult in fight providence. Changes in direction to note around obstacles shall be modely with condult and light bodies. Condult shall be retirated in a neal and workmanise manner, papeled and perpendicular to structure wall and cellar firsts. All condult in hall be fished to describationing in that of condults shall be improved to base by prevented madiscentia too bushing on in table on all powerbase makes been located on a outside and public provinced madiscential too bushing on in table on all powerbase makes been located on a outside and public provinced madiscential too bushing on in table on all powerbase makes been located on a outside on the provinced madiscential too bushing to make the provinced madiscential and and public provinced madiscential to a bushing on the provinced made to a bushing or public provinced madiscential to bushing to a bushing to the provinced madiscential too a bushing or public provinced madiscential to bushing to the public pub
- Conductors shall be pulled in accordance with accepted good practice.

to 8 hidge: Inc. Cobe Inor. In		1								
liliii laanaal	ഒ	ice Bridge:	Cable Tray:	Wa1/Partition:	Fence:	Wood/Iron Fence:	Leave Area:	Power:	Telco:	Hybrid:
	Graphics Legend	KXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		***************************************	 	- 1		Par	<u>ē</u>	₹

Acronym Legend

(P):			_		_			_	CDMA: C	_	880:
roposed	New	Aulfl Modal Base Statlon	tybrid line	leating Ventilation At Conditioning	Global Positioning System	iround	Edsting	Concrete Masonry Unit	Code Division Multiple Access	Cabinet	Battery Backup Unit
	HSM:	Η̈́Ω	Æ.	RRH	RF.	R.	RET:	RAD:	PWR:	PRI:	PPC:
	Hydrogen Storage Module	Hydrogen Fuel Cell	Telco	Remote Radio Head	Reinforced Fiberglass Panel	Radio Frequency	Remote Electrical Tilt	Radiation Center	Power	Legacy Primary Cabinet	Power Protection Cabinet

Sprint

12657 Alcosta Bivd., Sulte 300 San Ramon, CA 94583

- Effeitor pull boxes and juli boxes in interior industrial areas shall be plated cost alloy, heavy duty,
 Ce effeitor pull boxes and juli boxes, in interior industrial areas shall be plated cost alloy, heavy duty,
 Ce outside and state of the plate of the

1330 North Broadway Suite 202 Walnut Creek, CA 945%

- Manufacturer for boxes and covers shall be Hoffman, Square "d", Grouse-Hinds, Cooper, Adalet, Appleton, O-Z Gedney, Raco, or approved equal.

Borges

ROJECT NO: HECKED BY:

EV DATE DESCRIPTION OF THE DES	7			_	_		
DESC SERVICES	٤	٥	_	2	ω	Ш	ŀ
DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION	DATE	01/29/14	02/05/14	06/26/14	09/03/14		
	DESCRIPTION	WINNESS CO STRAITM		100% CD SUB REV 1	IOTA CO SIB REV 2		ľ

09/03/14 100% CD SUS REV 2

an Crisse and


PESCON UNUSS HEY ARE ACTING UNDER HE DESCON UNUSS HEY ARE ACTING UNDER HE DESCOND OF A LICENSED PROFESSIONAL ENGINEER, TO ALTER HIS DOCUMBER.


SF36XC032-B MELROSE PLACE


S460 BANCROFF AVENUE OAKLAND, CA 94601 SHEET TITLE


GENERAL NOTES 2


GN-2


















Transmit Receive втѕ Туре Region Market Length Ft. CL Height Weight of entire AISG cable. Lbs. Coax Jumper Diameter. Inches AISG Cable Coax Jumper Weight Coax Jumper Length. Feet. Diameter. Inches. RF Path Information BBU Kit Š General Site Information Antenna etilt Antenna Mechanical Downtilt Antenna Azimuth Antenna Mounting Kit Weight. Lbs. Antenna Weight, Inches Antenna Dimensions, Inches Antenna Sector Information AISG Cable length. AISG Diameter. Inches. AISG Cable Qty Coax Jumper Oty Coax Jumper Weight per foot, Lbs. Cable Qty Power and Fiber Cable RRH Mount Weight. Lbs. RRH Weight. lbs. RRH Qty Growth Cabinet Weight Growth Cabinet Dimensions Growth Cabinet BBU Dimensions BBU Kit Qty Base Equipment Structure Type intenna qty Intenna make/model rowth Cabinet Qty 2496 Mhz - 2690 Mhz 2496 Mhz - 2690 Mhz SF36XC032 SF Bay West STANDARD ROOFTOP Siterra SR Equipment type
Equipment Vendor KMW ET-X-WM-18-65-8P 61" x 12" x 4" 36 ~11 lb estimate. TBD. 50 BD 0.5 mmscope ATCB-B01-006 15.5" x 18.6" x 7.48" 54 3.5" × 17.1" × 15.2" n derived from existin NA NA NA Equipment Vendor 12.32 UADU 0.315 320 27 ප **RFDS Sheet** Longitude LL SITE ID Lattitude Outdoor Macro Samsung Sector 2 KMW ET-X-WM-18-65-8P GC to verify jumper length and quantity Specs as provided by Sprint is 15.03" x 21.26" x 8.03" Weight: 59.5 LBS calculated as antenna height plus 20%) 61" x 12" x 4" 36 ~11 lb estimate. TBD. 50 Samsung 37.7721667 -122.1986667 Top Hat Qty
Top Hat Dimenstions
Top Hat Weight (Ibs) needed by added Equipment Sector 3 KMW ET-X-WM-18-65-8P 61" x 12" x 4"
36
~11 lb estimate. TBD.
50 140 Specs as provided by Sprint is 61" x 12" x 4,3" Antenna Weight: 36.4 lbs Antenna mounting kit weight: 13.2 lbs Borges 1330 North Broadway Suite 202 Walnut Creek, CA 94596 Sprint IT IS A VOCATION OF LAW FOR ANY PRECON. UNLESS THEY ARE ACTING UNDER THE DIRECTION OF A LICENSID PROFESSIONAL ENGINEER, TO ALTER THIS DOCUMBER. A COMMAND PROJECT NO: 13065-108 SF36XC032-B 12457 Alcosta Blvd., Sulle 300 San Ramon, CA 94583 ANTENNA SCHEDULE & PARTS LIST 5460 BANCROFI AVENUE OAKLAND, CA 94601 MELROSE PLACE RF-1 픞

ANTENNA SCHEDULE & PARTS LIST

NOSCALE

>



17 ANTENNA GROUNDING PLAN SERIOL PER CALE DOWN ALL WYSO ANGE OF WITHOUT PER CALE TO THE CALE PARALLEL HORIZONIAL
CONDUCTORS
ARALLEL THROUGH CONNECTION
OF HORIZONAL CABLES
TYPE PT THROUGH CASEE TO GROUND ROD OF GROUND ROD OF GROUND ROD THREE OF OF GROUND ROD THREE OF CADWELD CONNECTIONS
OR APPROVED EQUAL TYPICAL CADWELD TYPE CONNECTIONS HORIZONTAL SITEEL SURFACE
TO FLATSTEEL SURFACE OR
HORIZONTAL PIPE
TYPE HS VERTICAL SIEEL SURFACE
CARLE DOWN AT 45°
TO VERTICAL STEEL SURFACE
INCLIDING PPE
INCLIDING PPE
TYPE VS COPPER_LUGS
TWO HOLE-LONG BARREL ENGTH
TYPE YA-2 BURNDY CONNECTIONS
OR APPROVED EQUAL BOND JUMPER
FELD FASRICATED GREEN
STRANDED INSULATED
TYPE 2-YA-2

GROUNDING NOTES

- 1 ALL ELECTRICAL AND GROUNDING AT THE CELL STE SHALL COMPLY WITH THE NATIONAL ELECTRICAL CODE (NEC), NATIONAL FIRE PROTECTION ASSOCIATION (NEPA) 780 (LATEST EDITION), AND MANUFACTURES SPECIFICATION.
- 2 FIRE, CANAS, IN REPORTS CANATIS WEED A SERVE ERRANCE HE ACEIVAGE GOODAD CONDUCTOR SHALL RECONNECTED TO GROUND ELECTROSS STEEL AND ANY LECT A PAREL IN REPORTS CANNET IS CONDIDED A SUPANEL THE GROUND WIRE SHALLES INSTALED IN THE ACTIVITIES CONJUIT, THE INSTALLATION SHALL BE FIRE LOCAL AND NAMEL MELECTROS COST (REPAYAR).
- CONTENIOR MELINO E RECOMMENDED POR GROUDING CONSECTION WHISE PRACTICAL DIRECTION ES CONSECTIONALE MADE HAVE CONSECTION THE PROPERTY OF CONSECTIONALE MADE HAVE CONSECTION THE PROPERTY OF CONSECTION C

The second second

1330 North Broadway Suite 202 Walnut Creek, CA 945%

Sprint 💮

12657 Alcosta Bivd., Suite 300 San Ramon, CA 94583

- AL GORDAND CONDUCTOR INSTITUTION DATA LESS IN LOCADITACION PLOTANTITUDA, AND INALI EL REALIZA STRANCIA AL RACIOLAL MITHANOS RESTO NAMO GENERICITANS. HE REMONDE AND IN A TRI ZERIANDINO CONDUCTOR SE PAC ACCIANT ANA TELEDIZI CO RODO PET REELE CONTITONS. GROWNING CONDUCTOR SMALL NOT MASE CONFACT WITH ANY MENULUC CONDUIT, SURVINCES DE CRAIN-PORT. HE ARBAN, CARES SMLTE GROUNDED AT HEITO, NO SOTTOM OF HE KETCAL RUYCO LICHMO PROTECTION, THE ARBONIC ALC. CARES AND THE RECOVERED A COPIES GROUND REAL AT HEIL AND THE RECOVER THE SOST OF A COPIES AND THE RECOVER AND THE RECOVER THE SOST OF A COPIES AND THE RECOVER AND T
- PROVIDE PVC SLEEVES WHERE GROUNDING CONDUCTORS PASS THROUGH THE BUILDING WALLS AND JOR CEILINGS,
- GROUND ANTENNA SAES, FRANES, CARLE RACES AND OTHER METALLIC COMPONENTS WITH #2 GROUNDING CONDUCTORS AND CONNECTION DRULLED SURFACE MOUNTED GROUND SMES, CONNECTION DEFAUS SHALL FOLLOW MANUFACTURESS SPECIFICATIONS FOR GROUNDING. INSTALL GROUND BUSHINGS ON ALL METALLIC CONDUITS AND BOND TO THE EQUIPMENT GROUND BUSS IN THE PANEL BOARD.
- 9. ALL PROPOSED GROUNDING CONDUCTORS SHALL BE ROUTED AND CONNECTED TO THE MAIN GROUND BAR OR EXITING GROUND RING.



GROUNDING LEGEND

MECHANICAL CONNECTION CADWELD CONNECTION (EXOTHERMIC WELD) EXISTING GROUND RING















OFFICE SUB-REV 2


- [P] GROUND BAR ON CABLE TRAY

RZH GROUNDING, PER 6/G-2 TYP.


SF36XC032-B MELROSE PLACE 5460 BANCROFF AVENUE OAKLAND, CA 94601


GROUNDING PLAN & NOTES SHEEL LILUE

G-1



.







Sprint

SF36XC032-B Melrose Place 5460 Bancroft Avenue, Oakland, CA 94601

ForzaTelecom 1330 N Broadway Ste. 202 Walnut Creek, CA 94596 info@photosims.com





Sprint

SF36XC032-B Melrose Place 5460 Bancroft Avenue, Oakland, CA 94601

09,03.203 ForzaTelecom 1330 N Broadway Ste, 202 Walnut Creek, CA 94596 info@photosIrns.com

Statement of Hammett & Edison, Inc., Consulting Engineers

The firm of Hammett & Edison, Inc., Consulting Engineers, has been retained on behalf of Sprint Nextel, a personal wireless telecommunications carrier, to evaluate proposed modifications to its existing base station (Site No. SF36xc032) located at 5460 Bancroft Avenue in Oakland, California, for compliance with appropriate guidelines limiting human exposure to radio frequency ("RF") electromagnetic fields.

Executive Summary

Sprint Nextel proposes to install additional directional panel antennas above the roof of the four-story residential building located at 5460 Bancroft Avenue in Oakland. The proposed operation will comply with the FCC guidelines limiting public exposure to RF energy.

Prevailing Exposure Standards

The U.S. Congress requires that the Federal Communications Commission ("FCC") evaluate its actions for possible significant impact on the environment. A summary of the FCC's exposure limits is shown in Figure 1. These limits apply for continuous exposures and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health. The most restrictive FCC limit for exposures of unlimited duration to radio frequency energy for several personal wireless services are as follows:

Wireless Service	Frequency Band	Occupational Limit	Public Limit
Microwave (Point-to-Point)	5,000-80,000 MHz	$5.00 \mathrm{mW/cm^2}$	$1.00 \mathrm{mW/cm^2}$
BRS (Broadband Radio)	2,600	5.00	1.00
WCS (Wireless Communication	n) 2,300	5.00	1.00
AWS (Advanced Wireless)	2,100	5.00	1.00
PCS (Personal Communication) 1,950	5.00	1.00
Cellular	870	2.90	0.58
SMR (Specialized Mobile Radi	o) 855	2.85	0.57
700 MHz	700	2.40	0.48
[most restrictive frequency rang	ge] 30-300	1.00	0.20

General Facility Requirements

Base stations typically consist of two distinct parts: the electronic transceivers (also called "radios" or "channels") that are connected to the traditional wired telephone lines, and the passive antennas that send the wireless signals created by the radios out to be received by individual subscriber units. The transceivers are often located at ground level and are connected to the antennas by coaxial cables. A small antenna for reception of GPS signals is also required, mounted with a clear view of the sky. Because of the short wavelength of the frequencies assigned by the FCC for wireless services, the



antennas require line-of-sight paths for their signals to propagate well and so are installed at some height above ground. The antennas are designed to concentrate their energy toward the horizon, with very little energy wasted toward the sky or the ground. This means that it is generally not possible for exposure conditions to approach the maximum permissible exposure limits without being physically very near the antennas.

Computer Modeling Method

The FCC provides direction for determining compliance in its Office of Engineering and Technology Bulletin No. 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radio Frequency Radiation," dated August 1997. Figure 2 attached describes the calculation methodologies, reflecting the facts that a directional antenna's radiation pattern is not fully formed at locations very close by (the "near-field" effect) and that at greater distances the power level from an energy source decreases with the square of the distance from it (the "inverse square law"). The conservative nature of this method for evaluating exposure conditions has been verified by numerous field tests.

Site and Facility Description

Based upon information provided by Sprint Nextel, including construction drawings by Borges Architectural Group, dated March 5, 2014, that carrier presently has three Andrew directional panel antennas — two Model RR65-18-00DPL2 and one Model FR65-17-00DP — installed within an enclosure, configured to resemble a chimney, above the roof of the four-story residential building located at 5460 Bancroft Avenue in Oakland. Sprint Nextel proposes to expand it existing enclosure and to install three KMW Model ET-X-WM-18-65-8P directional panel antennas next to its existing antennas. The existing antennas would remain mounted at an effective height of about 52½ feet above ground, 7½ feet above the roof, and the proposed antennas would be mounted at an effective height of about 50 feet above ground, 5 feet above the roof. The six antennas would be oriented in pairs (one of each type) with up to 2° downtilt¹ toward 80°T, 155°T, and 320°T. The maximum effective radiated power in any direction would be 8,230 watts, representing simultaneous operation at 1,540 watts for BRS and 6,690 watts for PCS. There are reported no other wireless telecommunications base stations at the site or nearby.

Study Results

For a person anywhere at ground, the maximum RF exposure level due to the proposed Sprint Nextel operation is calculated to be 0.0067 mW/cm², which is 0.67% of the applicable public exposure limit.

¹ Assumed for the purposes of this study.



The maximum calculated level at any nearby building² is 19% of the public exposure limit. It should be noted that these results include several "worst-case" assumptions and therefore are expected to overstate actual power density levels from the proposed operation. Levels are calculated to exceed the applicable public exposure limit on the roof of the subject building in front of the antennas, as shown in Figure 3.

Recommended Mitigation Measures

It is recommended that barricades be erected, as shown in Figure 3, to preclude public access in front of the antennas. To prevent occupational exposures in excess of the FCC guidelines, it is recommended that appropriate RF safety training be provided to all authorized personnel who may need access to the areas within the barricades, including employees and contractors of Sprint Nextel as well as roofers, HVAC workers, and building maintenance staff. No access within 10 feet directly in front of the antennas themselves, such as might occur during maintenance work within the barricades, should be allowed while the base station is in operation, unless other measures can be demonstrated to ensure that occupational protection requirements are met. Posting explanatory signs³ at the roof access door, on the barricades, and on the enclosure in front of the antennas, such that the signs would be readily visible from any angle of approach to persons who might need to work within that distance, would be sufficient to meet FCC-adopted guidelines.

Conclusion

Based on the information and analysis above, it is the undersigned's professional opinion that the proposed operation of the Sprint Nextel base station located at 5460 Bancroft Avenue in Oakland, California, can comply with the prevailing standards for limiting human exposure to radio frequency energy and, therefore, need not for this reason cause a significant impact on the environment. The highest calculated level in publicly accessible areas is much less than the prevailing standards allow for exposures of unlimited duration. This finding is consistent with measurements of actual exposure conditions taken at other operating base stations. Erecting barricades is recommended to establish compliance with public exposure limitations and training of authorized personnel and posting explanatory signs is recommended to establish compliance with occupational exposure limitations.

³ Signs should comply with OET-65 color, symbol, and content recommendations. Contact information should be provided (e.g., a telephone number) to arrange for access to restricted areas. The selection of language(s) is not an engineering matter, and guidance from the landlord, local zoning or health authority, or appropriate professionals may be required.



² Including the four-story building located at least 70 feet to the west, based on photographs from Google Maps.

Authorship

The undersigned author of this statement is a qualified Professional Engineer, holding California Registration No. E-20309, which expires on March 31, 2015. This work has been carried out under his direction, and all statements are true and correct of his own knowledge except, where noted, when data has been supplied by others, which data he believes to be correct.

April 4, 2014




FCC Radio Frequency Protection Guide

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The FCC adopted the limits from Report No. 86, "Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," published in 1986 by the Congressionally chartered National Council on Radiation Protection and Measurements ("NCRP"). Separate limits apply for occupational and public exposure conditions, with the latter limits generally five times more restrictive. The more recent standard, developed by the Institute of Electrical and Electronics Engineers and approved as American National Standard ANSI/IEEE C95.1-2006, "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," includes similar limits. These limits apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health.

As shown in the table and chart below, separate limits apply for occupational and public exposure conditions, with the latter limits (in *italics* and/or dashed) up to five times more restrictive:

Frequency	_Electro	magnetic	Fields (f is fr	equency of	emission in	MHz)	
Applicable Range (MHz)	Electric Field Strength (V/m)		Field S	netic trength /m)	Equivalent Far-Fie Power Density (mW/cm ²)		
0.3 - 1.34	614	614	1.63	1.63	100	100	
1.34 - 3.0	614	823.8/f	1.63	2.19/f	100	$180/f^2$	
3.0 - 30	1842/f	823.8/f	4.89/ f	2.19/f	900/ f ²	$180/f^2$	
30 - 300	61.4	27.5	0.163	0.0729	1.0	0.2	
300 - 1,500	3.54 √ f	1.59√f	√f/106	$\sqrt{f/238}$	f/300	f/1500	
1,500 - 100,000	137	61.4	0.364	0.163	5.0	1.0	



Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits, and higher levels also are allowed for exposures to small areas, such that the spatially averaged levels do not exceed the limits. However, neither of these allowances is incorporated in the conservative calculation formulas in the FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) for projecting field levels. Hammett & Edison has built those formulas into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radio sources. The program allows for the description of buildings and uneven terrain, if required to obtain more accurate projections.



HAMMETT & EDISON, INC.

RFR.CALC[™] Calculation Methodology

Assessment by Calculation of Compliance with FCC Exposure Guidelines

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The maximum permissible exposure limits adopted by the FCC (see Figure 1) apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health. Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits.

Near Field.

Prediction methods have been developed for the near field zone of panel (directional) and whip (omnidirectional) antennas, typical at wireless telecommunications base stations, as well as dish (aperture) antennas, typically used for microwave links. The antenna patterns are not fully formed in the near field at these antennas, and the FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) gives suitable formulas for calculating power density within such zones.

For a panel or whip antenna, power density
$$S = \frac{180}{\theta_{BW}} \times \frac{0.1 \times P_{net}}{\pi \times D \times h}$$
, in mW/cm²,

and for an aperture antenna, maximum power density $S_{max} = \frac{0.1 \times 16 \times \eta \times P_{net}}{\pi \times h^2}$, in mW/cm²,

where θ_{BW} = half-power beamwidth of the antenna, in degrees, and

P_{net} = net power input to the antenna, in watts,

D = distance from antenna, in meters,

h = aperture height of the antenna, in meters, and

 η = aperture efficiency (unitless, typically 0.5-0.8).

The factor of 0.1 in the numerators converts to the desired units of power density.

Far Field.

OET-65 gives this formula for calculating power density in the far field of an individual RF source:

power density
$$S = \frac{2.56 \times 1.64 \times 100 \times RFF^2 \times ERP}{4 \times \pi \times D^2}$$
, in mW/cm²,


where ERP = total ERP (all polarizations), in kilowatts,

RFF = relative field factor at the direction to the actual point of calculation, and

D = distance from the center of radiation to the point of calculation, in meters.

The factor of 2.56 accounts for the increase in power density due to ground reflection, assuming a reflection coefficient of $1.6 (1.6 \times 1.6 = 2.56)$. The factor of 1.64 is the gain of a half-wave dipole relative to an isotropic radiator. The factor of 100 in the numerator converts to the desired units of power density. This formula has been built into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radiation sources. The program also allows for the description of uneven terrain in the vicinity, to obtain more accurate projections.

Calculated RF Exposure Levels and Suggested Minimum Locations for Barricades (green)





Notes:

Base drawing from Borges Architectural Group, dated March 5, 2014. Barricades should be erected as shown to preclude access by the public to areas in front of the antennas.

Explanatory signs should be posted at the roof access doors, on the barricades, and on the screen and enclosure in front of the antennas, readily visible to authorized workers needing access. See text.

